



## Features

- Aluminum Phone Mounting Plate with Standard Wall Mount Phone Jack
- Water Resistant Enclosure Design with Gasketed Lid
- Stainless Steel Hinge and Quick Release Latches with Padlock Hasps
- Fiberglass Reinforced Polyester, FRP
- Available with either Service or Emergency Phone Labels
- Weatherproof, UV Stable and Highly Corrosion Resistant
- NEMA 4, 4X / IP66 Rated
- Includes Cable Gland and Stainless Steel Mounting Feet
- Pole Mounting Kit Available

## Description

---

The **Altelix NF141206-T01** Outdoor Weatherproof Phone Enclosure is ideal for deploying service and emergency telephones in outdoor locations and harsh environments. This rugged NEMA 4X enclosure is molded from durable and UV resistant fiberglass reinforced polyester (FRP) with a UL94-5V flame rating. It features a stainless steel continuous door hinge and stainless steel latches with provision for padlocks. The door is fully gasketed making this enclosure suitable for use in dusty and wet areas. This model features a finished aluminum mounting plate and a wall mount RJ11 jack.

This rugged dustproof and waterproof telephone enclosure is ideal for commercial applications including public pool decks, parking garages, resort properties, marinas, golf courses and public areas. Industrial uses include tunnels and mining, railway and subway stations, refineries, cement and chemical plants, treatment facilities and loading docks.

### Labels

The NF141206-T01 is available with either a red and white Emergency Phone label or a green and white Service Phone label. Applied to the enclosure door, these labels are weatherproof and UV resistant.

### Mounting

Stainless steel brackets are included for secure wall mounting. Optional flange and pole mounting kits are available.

## Specifications

---

<b>Models / Labels</b>	NF141206-T01-1 / Emergency Phone Label NF141206-T01-2 / Service Phone Label
<b>Material</b>	Fiberglass Reinforced Polyester
<b>Color</b>	Gray
<b>Outer Dimensions</b>	15.7 x 13.8 x 6.5 Inches (401 x 352 x 165 mm)
<b>Inner Dimensions*</b>	13.0 x 11.0 x 4.9 Inches (330 x 279 x 124 mm)
<b>Weight</b>	10.2 lbs. (4.6 kg)
<b>Ratings</b>	Meets NEMA 1, 2, 4, 4X, 12, 13, and IP65, IP66
<b>Flame Rating</b>	UL94-5V

\*Interior dimensions represent maximum space available for equipment.