

14x12x6 Fiberglass Weatherproof NEMA 4X Enclosure with
Blank Galvanized Steel Equipment Mounting Plate



Features

- Water Resistant JIC Enclosure Design with Gasketed Lid
- Stainless Steel Hinge and Quick Release Latches with Padlock Hasps
- Fiberglass Reinforced Polyester, FRP
- Includes 18 Gauge Galvanized Steel Blank Equipment Mounting Plate
- Weatherproof, UV Stable and Highly Corrosion Resistant
- Meets NEMA 1, 2, 4, 4X, 12, 13, and IP65, IP66
- Includes Stainless Steel Mounting Feet
- RF Transparent Enclosure
- Pole Mounting Kit Available

Description

The **Altelix NF141206G NEMA 4X Weatherproof Enclosure** is ideal for protecting equipment from harsh environments and tampering. This rugged NEMA box is molded from durable and UV resistant fiberglass reinforced polyester (FRP) with a UL94-5V flame rating. It features a gasketed door with stainless steel continuous hinge and stainless steel quick release latches with padlock hasps. The generous size of this enclosure accommodates a wide range of equipment.

This JIC style enclosure is dent-proof, corrosion resistant and UV stable. The FRP material is non-conductive and RF transparent. It is suitable for use in the harshest outdoor environments. It can be drilled and modified by the installer to suit unique site requirements.

Blank Galvanized Steel Equipment Plate

This model features a rugged 18 gauge galvanized steel blank equipment mounting plate. Durable and corrosion resistant, these blank plates can be drilled and modified by the installer to suit unique site requirements.

Mounting

Stainless steel brackets are included for secure wall mounting. Optional flange and pole mounting kits are available.

Specifications

Material	Fiberglass Reinforced Polyester
Color	Gray
Outer Dimensions	15.7 x 13.8 x 6.5 Inches (401 x 352 x 165 mm)
Inner Dimensions*	13.0 x 11.0 x 4.9 Inches (330 x 279 x 124 mm)
Weight	10.2 lbs. (4.6 kg)
Mounting Plate Material	18 Gauge Galvanized Steel
Mounting Plate Dimensions	10.9 x 12.8 inch (267 x 324 mm)
Ratings	Meets NEMA 1, 2, 4, 4X, 12, 13, and IP65, IP66
Flame Rating	UL94-5V
Industry Certifications	CE

*Interior dimensions represent maximum space available for equipment.