



Features

- (2) 4 inch Vents with Rain Shields and Screens
- Features a No-Drill PVC Non-Metallic Equipment Mounting Plate – Mount your equipment securely without the need for drilling!
- RF Transparent Enclosure
- Water Resistant JIC Enclosure Design with Gasketed Lid
- Stainless Steel Hinge and Quick Release Latches with Padlock Hasps
- Fiberglass Reinforced Polyester, FRP
- Weatherproof, UV Stable and Highly Corrosion Resistant
- NEMA Type 3R, 3RX / IP24 Rated
- Includes Stainless Steel Mounting Feet
- Optional Pole Mounting Kit Available

Description

The **Altelix NF141206VM1** Vented Weatherproof NEMA Enclosure features two 4 inch air vents covered by rain shields, with cleanable screens. It is ideal for protecting equipment from harsh environments and tampering, while allowing ventilation for installed equipment or batteries.

Extreme Protection Built to Last - This JIC style enclosure is dent-proof, corrosion resistant and UV stable. It is ideal for protecting equipment from harsh environments and tampering. This rugged NEMA box is molded from durable and UV resistant fiberglass reinforced polyester (FRP) with a UL94-5V flame rating. The FRP material is non-conductive and RF transparent. It features a gasketed door with stainless steel continuous hinge and stainless steel quick release latches with padlock hasps.

No-Drill Non-Metallic Equipment Plate - This configuration consists of the vented FRP enclosure with hinged lid and a 1/4" thick non-metallic PVC plate for mounting and securing equipment. Due to the "No-Drill" design of this PVC plate, mounting radios and other equipment can be done simply by using self-tapping screws.

Wireless Compatibility - This RF transparent enclosure and non-metallic equipment mounting plate are ideal for wireless applications including WiFi, RFID, IoT, Cellular and more. The non-metallic materials will not interfere with the operation of wireless gear. The generous size of this enclosure accommodates a wide range of equipment.

Mounting - Stainless steel brackets are included for secure wall mounting. Optional flange and pole mounting kits are available.

Specifications

Material	Fiberglass Reinforced Polyester
Color	Gray
Outer Dimensions	15.7 x 13.8 x 8.0 Inches (401 x 352 x 205 mm)
Inner Dimensions*	13.0 x 11.0 x 5.0 Inches (330 x 279 x 128 mm)
Mounting Plate Material	0.25 inch (6.4 mm) PVC
Mounting Plate Dimensions	10.9 x 12.8 inch (267 x 324 mm)
Weight	10.7 lbs. (4.8 kg)
Ratings	NEMA 3R, 3RX / IP24
Flame Rating	UL94-5V
Industry Certifications	CE

*Interior dimensions represent maximum space available for equipment.