


## 14x12x6 Fiberglass Weatherproof Vented RF Transparent Enclosure with 120 VAC Outlets, Power Cord and Non-Metallic Equipment Mounting Plate



### Features

- No Electrical Wiring Required
- Two (2) 4" Vents with Rain Shields and Screens
- Pre-Wired 120VAC Outlet with 5 Foot Power Cord
- Removable 120VAC Terminal Block
- Easy to Drill RF Transparent 5mm Thick Non-Metallic Polyester Equipment Mounting Plate
- Stainless Steel Hinge and Quick Release Latches with Padlock Hasps
- Fiberglass Reinforced Polyester, FRP
- Weatherproof, UV Stable and Highly Corrosion Resistant
- NEMA Type 3R, 3RX / IP24 Rated
- Includes Cable Glands and Stainless Steel Mounting Feet
- RF Transparent Enclosure
- Pole Mounting Kit Available

## Description

---

The **Altelix NF141206VMA1C** Enclosure is ideal for rapid deployment because no wiring is required. Simply mount the enclosure and plug the pre-wired 5 foot power cord into a nearby outlet. The 0.20" (5.0mm) thick polyester non-metallic RF transparent equipment mounting plate features two pre-wired 120VAC power outlets for your equipment.

**Get your project up and running quickly** and transition to hard-wired later if needed. The power cord can be easily removed, and the quick-connect terminal strip simplifies hard-wiring by a qualified installer.

### Ventilation

This enclosure features two 4" air vents. Rain shrouds keep rain water from entering the enclosure while allowing ventilation for installed equipment.

### Wireless Compatibility

This RF transparent enclosure and non-metallic equipment mounting plate are ideal for wireless applications including WiFi, RFID, IoT, Cellular and more. The non-metallic materials will not interfere with the operation of wireless gear.

**Extreme Protection Built to Last** - This rugged JIC style NEMA box is molded from durable UV stable and corrosion resistant fiberglass reinforced polyester (FRP) with a UL94-5V flame rating. The FRP material is dent-proof, non-conductive and RF transparent for compatibility with wireless equipment. It can be easily drilled and modified by the installer as needed. It features a gasketed door with stainless steel continuous hinge and stainless steel quick release latches with padlock hasps. The generous size of this enclosure accommodates a wide range of equipment.

## Specifications

---

<b>Material</b>	Fiberglass Reinforced Polyester
<b>Color</b>	Gray
<b>Voltage</b>	120VAC
<b>Max Load</b>	10A @ 120VAC
<b>Outer Dimensions</b>	15.7 x 13.8 x 8.0 Inches (401 x 352 x 205 mm)
<b>Inner Dimensions*</b>	13.0 x 11.0 x 4.2 Inches (330 x 279 x 106 mm)
<b>Mounting Plate Material</b>	0.20 in (2.5 mm) Polyester
<b>Mounting Plate Dimensions</b>	10.9 x 12.8 in. (276 x 324 mm)
<b>Weight</b>	11.0 lbs. (5.0 kg)
<b>Power Cord Length</b>	5 Feet (1.5m)
<b>Terminal Block Wire Range / Strip Length</b>	12-18 AWG / 6-7mm
<b>Ratings</b>	NEMA Type 3R, 3RX / IP24
<b>Flame Rating</b>	UL94-5V

\*See drawing for detailed dimensions of maximum space available for equipment.