



Features

- Thermostat Controlled Cooling Fan
- (2) 4" Vents with Rain Shields and Screens
- (4) Pre-Wired 120VAC Outlets with Power Cord and Removable 120VAC Terminal Block
- Aluminum Equipment Mounting Plate
- Extra Deep Extended Lid for Increased Equipment Clearance
- Stainless Steel Hinges with High Quality 316 Steel Hinge Pins
- Stainless Steel Quick Release Latches with Padlock Hasps
- Fiberglass Reinforced Polyester, FRP
- Weatherproof, UV Stable and Highly Corrosion Resistant
- NEMA Type 3R, 3RX / IP24 Rated
- Includes Cable Glands and Stainless Steel Mounting Feet
- RF Transparent Enclosure
- Pole Mounting Kit Available

Description

The **Altelix NF141210VFA1C** Fan Cooled Vented NEMA Enclosure is ideal for rapid deployment because no wiring is required. Simply mount the enclosure and plug the pre-wired 5 foot power cord into a nearby outlet. The aluminum equipment mounting plate features four pre-wired 120VAC power outlets for your equipment.

Get your project up and running quickly and transition to hard-wired later if needed. The power cord can be easily removed, and the quick-connect terminal strip simplifies hard-wiring by a qualified installer.

Cooling Fan with Thermostat Control - This enclosure features two 4" vents and a thermostat controlled cooling fan which helps maintain lower internal temperatures. The fan turns on when the internal temperature reaches 100°F (38°C) and turns off when it drops to 79°F (26°C). Rain shrouds keep rain water from entering the enclosure while allowing ventilation for installed equipment. The fan is wired internally, leaving all 4 power outlets available for installed equipment.

Extreme Protection Built to Last - This rugged JIC style NEMA box is molded from durable UV stable and corrosion resistant fiberglass reinforced polyester (FRP) with a UL94-5V flame rating. The FRP material is dent-proof, non-conductive and RF transparent for compatibility with wireless equipment. It can be easily drilled and modified by the installer as needed. It features a gasketed door with stainless steel continuous hinge and stainless-steel quick release latches with padlock hasps.

Increased Interior Space - The NF141210 series enclosures feature an extra deep lid, almost 2 inches deeper than our NF141208 series enclosures. With the generous size of this enclosure and extended lid the NF141210 can accommodate a wide range of equipment.

Specifications

| | |
|---|--|
| Material | Fiberglass Reinforced Polyester |
| Color | Gray |
| Voltage | 120VAC |
| Max Load | 10A @ 120VAC |
| Cooling Fan Turn-On Temperature | 100°F (38°C) |
| Cooling Fan Turn-Off Temperature | 79°F (26°C) |
| Outer Dimensions | 15.7 x 13.8 x 12.2 Inches (401 x 352 x 311 mm) |
| Inner Dimensions | 13.0 x 11.0 x 6.9 Inches (330 x 279 x 177 mm) |
| Mounting Plate Material | 0.10 in (2.5 mm) Aluminum |
| Mounting Plate Dimensions | 10.9 x 12.8 in. (276 x 324 mm) |
| Weight | 14 lbs. (6.3 kg) |
| Power Cord Length | 5 Feet (1.5m) |
| Terminal Block Wire Range | 12-18 AWG |
| Terminal Block Wire Strip Length | 6-7mm |
| Ratings | NEMA Type 3R, 3RX / IP24 |
| Flame Rating | UL94-5V |

*See drawing for detailed dimensions of maximum space available for equipment.