



Features

- (2) 4" Vents with Rain Shield and Screens
- Water Resistant JIC Enclosure Design with Gasketed Lid
- Extra Deep Extended Lid for Increased Equipment Clearance
- Stainless Steel Hinges with High Quality 316 Steel Hinge Pins
- Stainless Steel Quick Release Latches with Padlock Hasps
- Fiberglass Reinforced Polyester, FRP
- Weatherproof, UV Stable and Highly Corrosion Resistant
- NEMA Type 3R, 3RX / IP24 Rated
- Includes Cable Glands and Stainless-Steel Mounting Feet
- RF Transparent Enclosure
- Pole Mounting Kit Available

Description

The **Altelix NF162012V** Weatherproof Enclosure is ideal for protecting equipment from harsh environments and tampering. This enclosure features two 4 inch air vents covered by rain shields with cleanable screens which help expel heat from the installed equipment.

Extreme Protection Built to Last

This rugged NEMA box is molded from durable and UV resistant fiberglass reinforced polyester (FRP) with a UL94-5V flame rating. These enclosures feature improved stainless-steel hinges with high quality 316 steel hinge pins for lasting durability in even the harshest of coastal conditions. The gasketed door includes stainless steel quick release latches with padlock hasps.

This JIC style enclosure is dent-proof, corrosion resistant and UV stable. The FRP material is non-conductive and RF transparent. It is suitable for use in the harshest outdoor environments. It can be drilled and modified by the installer to suit unique site requirements.

Increased Interior Space

The NF162012V series enclosures feature an extra deep lid, over 3 inches deep. With the generous size of this enclosure and extended lid the NF162012V can accommodate a wide range of equipment.

Mounting

Stainless steel brackets are included for secure wall mounting. Optional flange and pole mounting kits are available.

Specifications

Material	Fiberglass Reinforced Polyester
Color	Gray
Outer Dimensions	17.9 x 21.8 x 14.3 Inches (454 x 553 x 363 mm)
Inner Dimensions	14.7 x 18.7 x 11.0 Inches (374 x 475 x 279 mm)
Weight	19.1 lbs. (8.7 kg)
Ratings	NEMA Type 3R, 3RX / IP24
Flame Rating	UL94-5V
Industry Certifications	CE