


16x20x12 Fiberglass Weatherproof Vented NEMA Enclosure with Dual Cooling Fans, 200W Heater and 120 VAC Outlets



Shown with mounting brackets installed.

## Features

- Dual Thermostat Controlled Cooling Fans and 200W Heating System
- (2) 4" Vents, Rain Shields and Screens
- (4) Pre-Wired 120VAC Outlets with Removable 120VAC Terminal Block
- Aluminum Equipment Mounting Plate
- Extra Deep Extended Lid for Increased Equipment Clearance
- Stainless Steel Hinges with High Quality 316 Steel Hinge Pins
- Stainless Steel Quick Release Latches with Padlock Hasps
- Fiberglass Reinforced Polyester, FRP
- Weatherproof, UV Stable and Highly Corrosion Resistant
- NEMA Type 3R, 3RX / IP24
- Includes Cable Glands and Stainless-Steel Mounting Feet
- RF Transparent Enclosure
- Pole Mounting Kit Available

## Description

The **Altelix NF162012VFHA1** Heated/Fan Cooled Vented NEMA Enclosure is ideal for outdoor environments where temperatures vary between hot and cold. It is equipped with thermostat-controlled heating and cooling systems to help keep your equipment within its operational temperature range. The aluminum equipment mounting plate features four pre-wired 120VAC power outlets for your equipment and a quick-connect top entry terminal block for easy wiring by a qualified installer. It is easily removable which helps simplify on-site wiring.

**Thermostat Controlled Cooling Fans and 200W Heating System** - Ideal for outdoor environments where temperatures vary between hot and cold, this enclosure features two 4" vents with rain shrouds and dual thermostat-controlled cooling fans which help maintain lower internal temperatures. Controlled by a separate thermostat, the 200W heating system is ideal for harsh weather and cold environments. Both the fan and heater are wired internally, leaving all the power outlets available for installed equipment.

**Extreme Protection Built to Last** - This rugged JIC style NEMA box is molded from durable UV stable and corrosion resistant fiberglass reinforced polyester (FRP) with a UL94-5V flame rating. The FRP material is dent-proof, non-conductive and RF transparent for compatibility with wireless equipment. It can be easily drilled and modified by the installer as needed. It features a gasketed door with stainless steel continuous hinge and stainless-steel quick release latches with padlock hasps.

**Increased Interior Space** - The NF162012V series enclosures feature an extra deep lid, over 3 inches deep. With the generous size of this enclosure and extended lid the NF162012VFHA1 can accommodate a wide range of equipment.

## Specifications

<b>Material</b>	Fiberglass Reinforced Polyester
<b>Color</b>	Gray
<b>Voltage / Max Load</b>	120VAC / 15A @ 120VAC
<b>Cooling Fan Turn-On Temperature</b>	100°F (38°C)
<b>Cooling Fan Turn-Off Temperature</b>	79°F (26°C)
<b>Heater Turn-On Temperature</b>	43°F (6°C)
<b>Heater Turn-Off Temperature</b>	59°F (15°C)
<b>Heater Power</b>	200 Watts
<b>Outer Dimensions</b>	17.9 x 21.8 x 14.3 Inches (454 x 553 x 363 mm)
<b>Inner Dimensions*</b>	14.7x 18.7 x 9.5 Inches (374 x 475 x 241 mm)
<b>Mounting Plate Material</b>	0.08 in (2.0 mm) Aluminum
<b>Mounting Plate Dimensions</b>	18.7 x 14.8 in. (475 x 378 mm)
<b>Weight</b>	21.6 lbs. (9.9 kg)
<b>Terminal Block Wire Range</b>	12-18 AWG
<b>Terminal Block Wire Strip Length</b>	6-7mm
<b>Ratings</b>	NEMA Type 3R, 3RX / IP24
<b>Flame Rating</b>	UL94-5V

\*Interior dimensions represent maximum space available for equipment.