NF201609-DIN

Altelix 20x16x9 Fiberglass Weatherproof NEMA DIN Rail Enclosure – Vented or Non-Vented







Features

- **Steel Din Rail Mounting Brackets with 16 Rail Mounting Positions**
- **Includes (3) Steel 35mm Top Hat DIN Rails and Screws**
- **Water-Resistant JIC Enclosure Design with Flat Gasketed Lid**
- **Fiberglass Reinforced Polyester (FRP) Construction**
- **Weatherproof, UV Stable and Highly Corrosion Resistant**
- **Vented and Non-Vented Configurations**
- **Non-Vented Models Rated NEMA 4X / IP66**
- **Vented Models Rated NEMA 3R / 3RX / IP24**
- **Raised Bosses with Threaded Brass Inserts for Mounting Plates and DIN Rail**
- **Stainless Steel Hinges with 316 Stainless Steel Hinge Pins**
- **Stainless Steel Quick-Release Latches with Padlock Hasps**
- **RF Transparent Enclosure**
- **Includes Stainless Steel Wall Mounting Feet**
- **Optional Pole Mount Available**

Altelix LLC USA: 866-660-9434 +1 561-660-9434 sales@altelix.com www.altelix.com
Copyright (C) 2026 Altelix LLC. All rights reserved. Altelix and the Altelix logo are Trademarks and/or Registered Trademarks of Altelix LLC.
Specifications are subject to change without notice. See www.altelix.com for most current information.

Description

The **Altelix 20x16x9 Fiberglass DIN Rail Enclosure** features two heavy-duty 12-gauge steel mounting brackets that provide 16 DIN rail mounting positions for flexible equipment placement. Three pre-cut 15-inch (381 mm) steel 35 mm top-hat DIN rails and mounting hardware are included.

Extreme Protection Built to Last
Molded from durable, UV-resistant fiberglass reinforced polyester (FRP) with a UL94-5V flame rating, this rugged enclosure is designed for demanding indoor and outdoor environments. Stainless steel hinges with 316 stainless steel hinge pins provide lasting corrosion resistance, while stainless steel quick-release latches with padlock hasps secure the flat gasketed lid. Non-vented models provide NEMA 4X / IP66 protection, while vented models allow passive airflow and are rated NEMA 3R / 3RX / IP24.

This JIC-style enclosure is dent-proof, corrosion-resistant and UV stable. The FRP material is non-conductive and RF transparent, making it suitable for use in harsh indoor and outdoor environments. It can be drilled and modified by the installer to suit unique site requirements.

Vented and Non-Vented Options
These enclosures are available in vented and non-vented configurations to suit different equipment and environmental requirements. Non-vented models provide NEMA 4X / IP66 protection, while vented models allow passive airflow and are rated NEMA 3R / 3RX / IP24. Weatherproof Protection. Non-vented configurations provide NEMA 4X / IP66 protection against rain, dust and water intrusion. Vented configurations are rated NEMA 3R / 3RX / IP24, providing weather protection while allowing passive airflow through the enclosure.

Mounting
Stainless steel brackets are included for secure wall mounting. Optional flange and pole mounting kits are available.

Customization
We offer custom enclosures for WiFi equipment, DIN Mount Industrial Controls, Telephone Call Boxes, IP Phones, Security & Safety, Building Automation and More. Options include equipment mounting plates, DIN rails, AC/DC power, vents, cooling fans, heaters. We also offer full customization, engineering and on-site CNC machining of enclosures and associated equipment, all with quick turnaround time. Please contact us with your unique requirements.

Altelix LLC USA: 866-660-9434 +1 561-660-9434 sales@altelix.com www.altelix.com
Copyright (C) 2026 Altelix LLC. All rights reserved. Altelix and the Altelix logo are Trademarks and/or Registered Trademarks of Altelix LLC.
Specifications are subject to change without notice. See www.altelix.com for most current information.

Product Images



Altelix LLC USA: 866-660-9434 +1 561-660-9434 sales@altelix.com www.altelix.com
Copyright (C) 2026 Altelix LLC. All rights reserved. Altelix and the Altelix logo are Trademarks and/or Registered Trademarks of Altelix LLC.
Specifications are subject to change without notice. See www.altelix.com for most current information.

Product Images



Altelix LLC USA: 866-660-9434 +1 561-660-9434 sales@altelix.com www.altelix.com
Copyright (C) 2026 Altelix LLC. All rights reserved. Altelix and the Altelix logo are Trademarks and/or Registered Trademarks of Altelix LLC.
Specifications are subject to change without notice. See www.altelix.com for most current information.

Specifications

Specifications	NF201609-DIN	NF201609V-DIN
Configuration	Non-Vented, DIN Rail	Vented, DIN Rail
Material	Fiberglass Reinforced Polyester	Fiberglass Reinforced Polyester
Color	Gray	Gray
Outer Dimensions (L x W x D)	21.79 x 17.89 x 9.25 Inches (553 x 454 x 235 mm)	21.79 x 17.89 x 10.44 Inches (553 x 454 x 265 mm)
Inner Dimensions* (L x W x D)	19.38 x 15.38 x 8.5 Inches (492 x 391 x 216 mm)	19.38 x 15.38 x 8.5 Inches (492 x 391 x 216 mm)
DIN Rail Length	15 in. (381 mm)	15 in. (381 mm)
DIN Rail Material	20 Gauge (0.04 inch) Steel	20 Gauge (0.04 inch) Steel
Weight	18.0 lbs. (8.2 kg)	18.6 lbs. (8.4 kg)
Ratings	NEMA Type 4, 4X / IP66	NEMA Type 3R, 3RX / IP24
Flame Rating	UL94-5V	UL94-5V
Industry Certifications	CE	CE

*Interior dimensions represent maximum space available for equipment.

Altelix LLC USA: 866-660-9434 +1 561-660-9434 sales@altelix.com www.altelix.com
Copyright (C) 2026 Altelix LLC. All rights reserved. Altelix and the Altelix logo are Trademarks and/or Registered Trademarks of Altelix LLC.
Specifications are subject to change without notice. See www.altelix.com for most current information.