20x16x12 Fiberglass Weatherproof NEMA 4X Enclosure
with Blank Aluminum Equipment Mounting Plate

Aluminum Equipment Mounting Plate

Raised Gasketed Lid for More Interior Space

Fiberglass Reinforced Polyester (FRP) Construction

Stainless Steel Latches

Shown with mounting brackets installed.

Features

- Water Resistant JIC Enclosure Design with Gasketed Lid
- Includes Easy to Drill Blank Aluminum Equipment Mounting Plate
- Extra Deep Extended Lid for Increased Equipment Clearance
- Stainless Steel Hinges with High Quality 316 Steel Hinge Pins
- Stainless Steel Quick Release Latches with Padlock Hasps
- Fiberglass Reinforced Polyester, FRP
- Weatherproof, UV Stable and Highly Corrosion Resistant
- Meets NEMA 1, 2, 4, 4X, 12, 13, and IP65, IP66
- Includes Cable Glands and Stainless-Steel Mounting Feet
- RF Transparent Enclosure
- Pole Mounting Kit Available

Description

The **Altelix NF201612P** NEMA 4X Weatherproof Enclosure is ideal for protecting equipment from harsh environments and tampering. This rugged NEMA box is molded from durable and UV resistant fiberglass reinforced polyester (FRP) with a UL94-5V flame rating. These enclosures feature improved stainless-steel hinges with high quality 316 steel hinge pins for lasting durability in even the harshest of coastal conditions. The gasketed door includes stainless steel quick release latches with padlock hasps.

This JIC style enclosure is dent-proof, corrosion resistant and UV stable. The FRP material is non-conductive and RF transparent. It is suitable for use in the harshest outdoor environments. It can be drilled and modified by the installer to suit unique site requirements.

Increased Interior Space
The NF201612 series enclosures feature an extra deep lid, over 3 inches deep. With the generous size of this enclosure and extended lid the NF201612P can accommodate a wide range of equipment.

Aluminum Equipment Mounting Plate
This enclosure features an easy to drill aluminum equipment mounting plate. The enclosure and plate can be drilled and modified by the installer to suit unique site requirements.

Mounting
Stainless steel brackets are included for secure wall mounting. Optional flange and pole mounting kits are available.

Specifications

Material	Fiberglass Reinforced Polyester
Color	Gray
Outer Dimensions	21.8 x 17.9 x 12.7 Inches (553 x 454 x 323 mm)
Inner Dimensions	18.7 x 14.7 x 12.0 Inches (475 x 374 x 305 mm)
Mounting Plate Material	0.08 in (2.0 mm) Aluminum
Mounting Plate Dimensions	18.7 x 14.8 in. (475 x 378 mm)
Weight	18.5 lbs. (8.4 kg)
Ratings	Meets NEMA 1, 2, 4, 4X, 12, 13, and IP65, IP66
Flame Rating	UL94-5V
Industry Certifications	CE