



Features

- Heavy Duty Fiberglass Reinforced Polyester (FRP) Construction
- Blank Galvanized Steel Equipment Mounting Plate
- Dual Quarter-Turn Door Latches with Removable Keys
- (4) Mounting Feet Included
- NEMA Type 3, 3X / IP65 Rated
- Optional Lockable Latch Sets Available
- Optional Equipment Mounting Plates and Pole Mount Kits Available

Description

The **Altelix NFC161608P** NEMA 3X / IP65 rated enclosure is molded from durable and UV resistant fiberglass reinforced polyester (FRP). The door is fully gasketed making this enclosure suitable for use indoors or outdoors. The lockable door features reinforced hinges and dual quarter-turn latches to secure the enclosure and is locked and unlocked using the included removable keys. A drip rail over the door provides additional protection against water dripping into the cabinet while the enclosure is wet.

Galvanized Steel Equipment Plate

This configuration consists of the fiberglass NEMA enclosure with hinged lid and a 16 Gauge (1.5mm thick) galvanized steel plate for mounting and securing equipment. The enclosure and plate can be drilled and modified by the installer to suit unique site requirements.

Mounting

Four mounting feet are included so that the enclosure can be securely mounted to a wall or other structure. Optional flange and pole mounting kits are available.

Optional Lockable Latches

For additional protection of internal equipment installed, optional keyed latch sets are available. These optional lockable latches are direct replacements for the standard quarter-turn latches that come pre-installed in the enclosure.

Specifications

| | |
|---|---|
| Material | Fiberglass Reinforced Polyester |
| Color | Light Gray |
| Outer Dimensions (Height x Width x Depth) | 15.7 x 15.8 x 7.9 Inches (398 x 402 x 200 mm) |
| Inner Dimensions* (Height x Width x Depth) | 12.2 x 14.3 x 5.7 Inches (311 x 364 x 146 mm) |
| Equipment Plate Material | 16 Gauge Galvanized Steel |
| Equipment Plate Dimensions | 13.7 x 13.6 In. (348 x 345 mm) |
| Weight | 12.0 lbs. (5.4 kg) |
| Ratings | NEMA Type 3, 3X / IP65 |

*Interior dimensions represent maximum space available for equipment.