



24x16x9 NEMA 3X Fiberglass Weatherproof Enclosure with Non-Metallic Equipment Mounting Plate



Features

- Heavy Duty Fiberglass Reinforced Polyester (FRP) Construction
- Blank Non-Metallic Polyester Equipment Mounting Plate
- Dual Quarter-Turn Door Latches with Removable Keys
- (4) Mounting Feet Included
- NEMA Type 3, 3X / IP65 Rated
- Optional Lockable Latch Sets Available
- Optional Equipment Mounting Plates and Pole Mount Kits Available



Description

The **Altelix NFC241609M** NEMA 3X / IP65 rated enclosure is molded from durable and UV resistant fiberglass reinforced polyester (FRP). The door is fully gasketed making this enclosure suitable for use indoors or outdoors. The lockable door features reinforced hinges and dual quarter-turn latches to secure the enclosure and is locked and unlocked using the included removable keys. A drip rail over the door provides additional protection against water dripping into the cabinet while the enclosure is wet.

Non-Metallic Equipment Plate

Included is a 0.16" (4.0mm) non-metallic polyester plate for mounting and securing equipment. The enclosure and plate can be drilled and modified by the installer to suit unique site requirements.

RF Transparent Design

The NFC241609M is ideal for WiFi applications. The non-metallic design of both the enclosure and equipment mounting plate will not interfere the radio's operation. In addition, mounting radios to polyester equipment mounting plate can be done simply by using self-tapping screws. Due to the large size of this enclosure, multiple wireless points can be mounted inside as well as additional networking equipment.

Mounting

Four mounting feet are included so that the enclosure can be securely mounted to a wall or other structure. Optional flange and pole mounting kits are available.

Optional Lockable Latches

For additional protection of internal equipment installed, optional keyed latch sets are available. These optional lockable latches are direct replacements for the standard quarter-turn latches that come pre-installed in the enclosure.

Specifications

Material	Fiberglass Reinforced Polyester
Color	Light Gray
Outer Dimensions (Height x Width x Depth)	23.7 x 15.8 x 9.0 Inches (602 x 399 x 230 mm)
Inner Dimensions* (Height x Width x Depth)	20.2 x 14.1 x 7.0 Inches (514 x 359 x 178 mm)
Equipment Plate Material	0.16 in. (4.0 mm) White Polyester
Equipment Plate Dimensions	15.2 x 20.1 In. (386 x 510 mm)
Weight	17.2 lbs. (7.8 kg)
Ratings	NEMA Type 3, 3X / IP65

^{*}Interior dimensions represent maximum space available for equipment.