



Features

- Heavy Duty Fiberglass Reinforced Polyester (FRP) Construction
- Dual Quarter-Turn Door Latches with Removable Keys
- Includes (3) 35mm Top Hat DIN Rails and Mounting Hardware
- Integral T-Slot Nut Mounting System with 20 Positions
- (4) Mounting Feet Included
- NEMA Type 3, 3X / IP65 Rated
- Optional Lockable Latch Sets Available
- Optional Equipment Mounting Plates and Pole Mount Kits Available

Description

The **Altelix NFC242009-DIN** NEMA 3X / IP65 rated enclosure is molded from durable and UV resistant fiberglass reinforced polyester (FRP). The door is fully gasketed making this enclosure suitable for use indoors or outdoors. The lockable door features reinforced hinges and dual quarter-turn latches to secure the enclosure and is locked and unlocked using the included removable keys. A drip rail over the door provides additional protection against water dripping into the cabinet while the enclosure is wet.

Includes (3) DIN Rails and Integral T-Slot Nut Mounting System

Included with this enclosure are (3) 19" long 20 gauge steel 35mm top hat DIN rails. They are easily installed to the interior of the enclosure without drilling or modification using the integral T-Slot Nut mounting system. This versatile mounting system is molded into the interior of the enclosure and runs the full length of the enclosure from top to bottom. This allows the DIN rails to be mounted easily in any of 20 locations providing the flexibility needed when configuring the enclosure for specific user requirements. Hardware for mounting the DIN rails is included.

Mounting

Four mounting feet are included so that the enclosure can be securely mounted to a wall or other structure. Optional flange and pole mounting kits are available.

Optional Lockable Latches

For additional protection of internal equipment installed, optional keyed latch sets are available. These optional lockable latches are direct replacements for the standard quarter-turn latches that come pre-installed in the enclosure.

Specifications

Material	Fiberglass Reinforced Polyester
Color	Light Gray
Outer Dimensions (Height x Width x Depth)	23.7 x 19.7 x 9.0 Inches (602 x 499 x 230 mm)
Inner Dimensions* (Height x Width x Depth)	20.5 x 18.0 x 7.2 Inches (520 x 457 x 183 mm)
DIN Rail Length	19 In. (483 mm)
DIN Rail Material	20 Gauge (0.04 in.) Steel
Weight	15.4 lbs. (7.0 kg)
Ratings	NEMA Type 3, 3X / IP65

*Interior dimensions represent maximum space available for equipment.