



## Features

- Features a No-Drill PVC Non-Metallic Equipment Mounting Plate
- (2) 2 1/4" Vents with Rain Shields and Screens
- Meets NEMA 3R, 3RX and IP24
- Weatherproof and UV Stable
- Durable Polycarbonate + ABS
- RF Transparent for Wireless Devices
- Gasketed Lid with Dual Latches
- Tamper-Proof Locking Screw with Key and Provision for Padlock
- Includes Wall Mounting Hardware, Cable Glands, Zip Ties, Cable Management Loops
- Optional Pole Mount Kit Available

## Description

The **Altelix NP100904VM** features two 2¼" inch air vents covered by rain shields, with cleanable screens. It is ideal for protecting small devices from harsh environments and tampering, while allowing ventilation for installed equipment or batteries.

**Construction and Features** - This enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless-steel security screw and provision for padlock. It meets or exceeds NEMA 3R, 3RX and IP24.

**No-Drill Non-Metallic Equipment Plate** - This configuration consists of the PC+ABS enclosure with hinged lid and a 1/4" thick non-metallic PVC plate for mounting and securing equipment. Due to the "No-Drill" design of this PVC plate, mounting radios and other equipment can be done simply by using self-tapping screws.

**RF Transparent Design** - The NP100904VM is ideal for WiFi applications. The non-metallic design of both the enclosure and equipment mounting plate will not interfere the radio's operation. In addition, mounting radios to PVC equipment mounting plate can be done simply by using self-tapping screws. The size of this enclosure will fit a wide range of popular wireless points on the market.

**Complete with Cable Glands and Wire Management Accessories** - This enclosure includes 4 weatherproof cable glands. Simply punch out the seal, run your cable, and hand tighten for a water-tight seal. For convenience, the included accessory kit contains wall anchors, zip ties, hook-and-loop wire management straps, door locking key and more.

**Pole Mount Available** - A pole mounting kit is also available for this enclosure. It attaches to the rear of the enclosure and allows it to be mounted to poles and fence posts up to 9.5 inches in diameter.

## Specifications

<b>Material</b>	Polycarbonate + ABS
<b>Color</b>	Gray (Additional colors available – see Altelix.com)
<b>Outer Dimensions</b> (Height x Width x Depth)	10.2 x 9.9 x 5.4 Inches (260 x 252 x 138 mm)
<b>Inner Dimensions*</b> (Height x Width x Depth)	7.5 x 6.5 x 3.0 Inches (190 x 165 x 76 mm)
<b>Mounting Plate Material</b>	0.25 in. (6.4 mm) PVC
<b>Weight</b>	2.3 lbs. (1.0 kg)
<b>Ratings</b>	Meets or Exceeds NEMA 3R, 3RX and IP24
<b>Flame Rating</b>	Meets UL94-V0
<b>Included Cable Glands</b>	(4) M24 x 1.5

\*Interior dimensions represent maximum space available for equipment.