



Features

- Includes Steel Pole Mount Bracket and 2 Stainless Steel Bands for Mounting on Poles Up To 9.5 Inches in Diameter.
- Meets NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66
- Weatherproof and UV Stable
- Durable Polycarbonate + ABS
- RF Transparent for Wireless Devices
- Gasketed Lid with Dual Latches
- Tamper-Proof Locking Screw with Key and Provision for Padlock
- Integral Mounting Feet
- Includes Cable Grommets, Zip Ties, Cable Management Loops

Description

Weatherproof Polycarbonate + ABS Construction for Extreme Durability

The **Altelix NP120905-PKIT** Plastic Utility Enclosure is an industrial quality general purpose weatherproof utility box designed to offer extreme protection for wiring, electronics and wireless devices in harsh environments. This kit includes the enclosure and the pole mount kit shown.

Construction and Features

This enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless steel security screw and provision for padlock. Integrated mounting feet simplify installation. It meets or exceeds NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66.

Complete with Cable Grommets and Wire Management Accessories

This enclosure includes 4 weatherproof cable grommets. Simply punch out the seal and run your cables. For convenience, the included accessory kit contains wall anchors, zip ties, hook-and-loop wire management straps, plastic wire management loops, door locking key and more.

Mounting

This NEMA Box Kit includes the NMKG-150-08 Pole Mounting Kit that supports installation on poles up to 9.5 inches in diameter. These removable steel pole mounting brackets includes two heavy duty stainless steel adjustable bands.

Specifications

Material	Polycarbonate + ABS
Color	Gray
Outer Dimensions (Height x Width x Depth)	13.1 x 10.2 x 4.7 Inches (334 x 259 x 120 mm)
Inner Dimensions* (Height x Width x Depth)	9.4 x 7.5 x 3.7 Inches (239 x 190 x 95 mm)
Weight (Enclosure & Pole Mount)	3.0 lbs. (1.3 kg)
Ratings	Meets or Exceeds NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66
Flame Rating	Meets UL94-V0

*Interior dimensions represent maximum space available for equipment.