## NP120905A1C-0C

# Altelix

12x9x5 NEMA 4X Polycarbonate + ABS Weatherproof Enclosure with 120VAC 3-Prong Power Plug & Power Cord



## **Features**

- Features a 1.5mm Thick Finished Aluminum Equipment Mounting Plate with a Pre-Wired
  120VAC Power Plug
- Prewired 5 Foot Power Cord
- Meets NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP62 and IP66
- Weatherproof and UV Stable Durable Polycarbonate + ABS
- RF Transparent for Wireless Devices
- Gasketed Lid with Dual Latches, Tamper-Proof Locking Screw with Key and Provision for Padlock
- Integral Mounting Feet
- Includes Wall Mounting Hardware, Cable Grommets and Glands, Zip Ties, Cable Management Straps
- Optional Pole Mount Kit Available



## **Description**

The **Altelix NP120905A1C-OC** Plastic Utility Enclosure is an industrial quality general purpose weatherproof utility box designed to offer extreme protection for wiring, electronic and wireless devices in harsh environments.

#### **Construction and Features**

This enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless-steel security screw and provision for padlock. Integrated mounting feet simplify installation. It meets or exceeds NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66.

#### 120VAC Power

This configuration consists of the PC+ABS NEMA enclosure with hinged lid and a 1.5mm thick aluminum plate with a pre-wired 3-prong 120VAC power plug. A 5 foot pre-wired power cord is included to power the enclosure, so no additional wiring is required. Cable grommets on the enclosure allows cables to be connected to internal devices. Knock-outs are also provided on the enclosure for additional wiring. Extra cable grommets and cable glands are included with the accessory kit.

### Complete with Cable Grommets, Cable Glands and Wire Management Accessories

For convenience, the included accessory kit contains wall anchors, zip ties, hook-and-loop wire management straps, door locking key and more.

## **Specifications**

Material	Polycarbonate + ABS
Color	Gray (Additional colors available – see Altelix.com)
Voltage	120VAC
Max Load	10A @ 120VAC
Outer Dimensions (Height x Width x Depth)	13.1 x 10.2 x 4.7 Inches (334 x 259 x 120 mm)
Inner Dimensions* (Height x Width x Depth)	8.5 x 7.5 x 3.7 Inches (216 x 190 x 95 mm)
Mounting Plate Material	0.06 in. (1.5 mm) Aluminum
Weight	3.1 lbs. (1.4 kg)
Power Cord Length	5 Feet (1.5m)
Ratings	Meets NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66
Flame Rating	Meets UL94-V0

<sup>\*</sup>Interior dimensions represent maximum space available for equipment.