



Features

- (2) 2¼" Vents with Rain Shields and Screens
- RF Transparent for Wireless Devices
- Meets NEMA 3R, 3RX and IP24
- Weatherproof and UV Stable
- Durable Polycarbonate + ABS
- Gasketed Lid with Dual Latches
- Tamper-Proof Locking Screw with Key and Provision for Padlock
- Integral Mounting Feet
- Includes Wall Mounting Hardware, Cable Grommets, Zip Ties, Cable Management Loops
- Optional Pole Mount Kit Available

Description

The **Altelix NP120905V** Plastic Utility Enclosure features two 2¼" inch air vents covered by rain shields, with cleanable screens. It is ideal for protecting small devices from harsh environments and tampering, while allowing ventilation for installed equipment or batteries.

Construction and Features

This enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless-steel security screw and provision for padlock. Integrated mounting feet simplify installation. It meets or exceeds NEMA 3R, 3RX and IP24.

Complete with Cable Grommets and Wire Management Accessories

This enclosure includes 4 weatherproof cable grommets. Simply punch out the seal and run your cables. For convenience, the included accessory kit contains wall anchors, zip ties, hook-and-loop wire management straps, plastic wire management loops, door locking key and more.

Pole Mount Available

A pole mounting kit is also available for this enclosure. Attaches to the rear of the enclosure, it allows it to be mounted to poles and fence posts up to 9.5 inches in diameter.

Specifications

| | |
|---|--|
| Material | Polycarbonate + ABS |
| Color | Gray (Additional colors available – see Altelix.com) |
| Outer Dimensions (Height x Width x Depth) | 13.1 x 10.2 x 5.9 Inches (334 x 259 x 151 mm) |
| Inner Dimensions* (Height x Width x Depth) | 9.4 x 7.5 x 3.7 Inches (239 x 190 x 95 mm) |
| Weight | 2.2 lbs. (1.0 kg) |
| Ratings | Meets or Exceeds NEMA 3R, 3RX and IP24 |
| Flame Rating | Meets UL94-V0 |

*Interior dimensions represent maximum space available for equipment.