



Features

- (2) 2¼" Vents with Rain Shields and Screens
- Features a 1.5mm Thick Finished Aluminum Equipment Mounting Plate with a Pre-Wired 120VAC Power Plug
- Prewired 5 Foot Power Cord
- Meets NEMA 3R, 3RX and IP24
- Weatherproof and UV Stable Durable Polycarbonate + ABS
- RF Transparent for Wireless Devices
- Gasketed Lid with Dual Latches, Tamper-Proof Locking Screw with Key and Provision for Padlock
- Integral Mounting Feet
- Includes Wall Mounting Hardware, Cable Grommets and Glands, Zip Ties, Cable Management Straps
- Optional Pole Mount Kit Available

Description

The **Altelix NP120905VA1C-0C** features two 2¼" inch air vents with rain shields and screens. It is ideal for protecting small devices from harsh environments and tampering, while allowing ventilation for installed equipment or batteries.

Construction and Features

This enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless-steel security screw and provision for padlock. Integrated mounting feet simplify installation.

120VAC Power

This configuration consists of the PC+ABS NEMA enclosure with hinged lid and a 1.5mm thick aluminum plate with a pre-wired 3-prong 120VAC power plug. A 5 foot pre-wired power cord is included to power the enclosure, so no additional wiring is required.

Complete with Cable Grommets, Cable Glands and Wire Management Accessories

For convenience, the included accessory kit contains wall anchors, zip ties, hook-and-loop wire management straps, door locking key and more.

Specifications

Material	Polycarbonate + ABS
Color	Gray (Additional colors available – see Altelix.com)
Voltage	120VAC
Max Load	10A @ 120VAC
Outer Dimensions (Height x Width x Depth)	13.1 x 10.2 x 5.9 Inches (334 x 259 x 151 mm)
Inner Dimensions* (Height x Width x Depth)	8.5 x 7.5 x 3.7 Inches (216 x 190 x 95 mm)
Mounting Plate Material	0.06 In. (1.5mm) Aluminum
Weight	3.3 lbs. (1.5 kg)
Power Cord Length	5 Feet (1.5m)
Ratings	Meets NEMA 3R, 3RX and IP24
Flame Rating	Meets UL94-V0

*Interior dimensions represent maximum space available for equipment.