



## Features

- (2) 2¼" Vents and Thermostat Controlled Cooling Fan
- Features a 1.5mm Thick Finished Aluminum Equipment Mounting Plate with a Pre-Wired 120VAC Power Plug
- Prewired 5 Foot Power Cord
- Meets NEMA 3R, 3RX and IP24
- Weatherproof and UV Stable Durable Polycarbonate + ABS
- RF Transparent for Wireless Devices
- Gasketed Lid with Dual Latches, Tamper-Proof Locking Screw with Key and Provision for Padlock
- Integral Mounting Feet
- Includes Wall Mounting Hardware, Cable Grommets and Glands, Zip Ties, Cable Management Straps
- Optional Pole Mount Kit Available

## Description

The **Altelix NP120905VFA1C-0C** features two 2¼" inch air vents and a thermostat-controlled cooling fan. It is ideal for protecting small devices from harsh environments and tampering, while allowing ventilation for installed equipment or batteries.

**Construction and Features** - This enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless-steel security screw and provision for padlock. Integrated mounting feet simplify installation.

**Cooling Fan Ventilation** - The NP120905VFA1C-0C features two 2¼" inch air vents and a thermostat-controlled cooling fan. The low noise, high airflow fan helps maintain lower internal temperatures. Rain shrouds on the front door keep rainwater from entering the enclosure.

**120VAC Power** - This configuration consists of the PC+ABS NEMA enclosure with hinged lid and a 1.5mm thick aluminum plate with a pre-wired 3-prong 120VAC power plug. A 5 foot pre-wired power cord is included to power the enclosure, so no additional wiring is required.

**Complete with Cable Grommets, Cable Glands and Wire Management Accessories** - For convenience, the included accessory kit contains wall anchors, zip ties, hook-and-loop wire management straps, door locking key and more.

## Specifications

<b>Material</b>	Polycarbonate + ABS
<b>Color</b>	Gray (Additional colors available – see Altelix.com)
<b>Cooling Fan Turn-On Temperature</b>	100°F (38°C)
<b>Cooling Fan Turn-Off Temperature</b>	79°F (26°C)
<b>Voltage</b>	120VAC
<b>Max Load</b>	10A @ 120VAC
<b>Outer Dimensions</b> (Height x Width x Depth)	13.1 x 10.2 x 5.9 Inches (334 x 259 x 151 mm)
<b>Inner Dimensions*</b> (Height x Width x Depth)	8.5 x 7.5 x 2.7 Inches (216 x 190 x 68 mm)
<b>Mounting Plate Material</b>	0.06 In. (1.5mm) Aluminum
<b>Weight</b>	3.7 lbs. (1.7 kg)
<b>Power Cord Length</b>	5 Feet (1.5m)
<b>Ratings</b>	Meets NEMA 3R, 3RX and IP24
<b>Flame Rating</b>	Meets UL94-V0

\*Interior dimensions represent maximum space available for equipment.