



## Features

- Features a 1.5mm Thick Finished Aluminum Equipment Mounting Plate with a Pre-Wired 120VAC Power Plug
- Prewired 5 Foot Power Cord
- Meets NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP62 and IP66
- Weatherproof and UV Stable Durable Polycarbonate + ABS
- RF Transparent for Wireless Devices
- Extra Deep Gasketed Lid with Dual Latches, Tamper-Proof Locking Screw with Key and Provision for Padlock
- Integral Mounting Feet
- Includes Wall Mounting Hardware, Cable Grommets and Glands, Zip Ties, Cable Management Straps
- Optional Pole Mount Kit Available

## Description

---

The **Altelix NP120907A1C-0C** Plastic Utility Enclosure is an industrial quality general purpose weatherproof utility box designed to offer extreme protection for wiring, electronic and wireless devices in harsh environments.

### Construction and Features

This enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless-steel security screw and provision for padlock. Integrated mounting feet simplify installation. It meets or exceeds NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66.

### 120VAC Power

This configuration consists of the PC+ABS NEMA enclosure with hinged lid and a 1.5mm thick aluminum plate with a pre-wired 120VAC 3-prong power plug. A 5 foot pre-wired power cord is included to power the enclosure, so no additional wiring is required. A cable grommet on the enclosure allows cables to be connected to internal devices. Knock-outs are also provided on the enclosure for additional wiring. Extra cable grommets are included with the accessory kit.

### Complete with Cable Grommets and Glands and Wire Management Straps

For convenience, the included accessory kit contains cable grommets and glands, wall anchors, zip ties, hook-and-loop wire management straps, door locking key and more.

## Specifications

---

<b>Material</b>	Polycarbonate + ABS
<b>Color</b>	Gray (Additional colors available – see Altelix.com)
<b>Voltage / Max Load</b>	120VAC / 10A @ 120VAC
<b>Outer Dimensions</b> (Height x Width x Depth)	13.1 x 10.2 x 6.8 Inches (334 x 259 x 172 mm)
<b>Inner Dimensions*</b> (Height x Width x Depth)	8.5 x 7.5 x 5.8 Inches (216 x 190 x 147 mm)
<b>Mounting Plate Material</b>	0.06 in. (1.5 mm) Aluminum
<b>Weight</b>	4.0 lbs. (1.8 kg)
<b>Power Cord Length</b>	5 Feet (1.5m)
<b>Ratings</b>	Meets NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66
<b>Flame Rating</b>	Meets UL94-V0

\*Interior dimensions represent maximum space available for equipment.