



Features

- Features a 1.5mm Thick Finished Aluminum Equipment Mounting Plate with a 120VAC Power Outlet and Prewired 5 Foot Power Cord
- (2) 2¼" Vents with Rain Shields
- Meets NEMA 3R, 3RX and IP24
- Weatherproof and UV Stable Durable Polycarbonate + ABS
- RF Transparent for Wireless Devices
- Extra Deep Gasketed Lid with Dual Latches, Tamper-Proof Locking Screw with Key and Provision for Padlock
- Integral Mounting Feet
- Includes Wall Mounting Hardware, Cable Grommets and Glands, Zip Ties, Cable Management Straps
- Optional Pole Mount Kit Available

Description

The **Altelix NP120907VA1C** features two 2¼" inch air vents covered by rain shields, with cleanable screens. It is ideal for protecting small devices from harsh environments and tampering, while allowing ventilation for installed equipment or batteries. It features an extra deep lid providing additional depth.

Construction and Features - This enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless steel security screw and provision for padlock. Integrated mounting feet simplify installation. It meets or exceeds NEMA 3X,3RX and IP24.

Power - This configuration consists of the PC+ABS NEMA enclosure with hinged lid and a 1.5mm thick aluminum plate with a 120VAC power outlet. A 5 foot pre-wired power cord is included to power the enclosure, so no additional wiring is required. A cable grommet on the enclosure allows cables to be connected to internal devices. Knock-outs are also provided on the enclosure for additional wiring. Extra cable grommets and cable glands are included with the accessory kit.

Complete with Cable Grommets, Cable Glands and Wire Management Accessories - For convenience, the included accessory kit contains wall anchors, zip ties, hook-and-loop wire management straps, door locking key and more.

Pole Mount Available - A pole mounting kit is also available for this enclosure. Attaches to the rear of the enclosure, it allows it to be mounted to poles and fence posts up to 9.5 inches in diameter.

Specifications

Material	Polycarbonate + ABS
Color	Gray (Additional colors available – see Altelix.com)
Voltage / Max Load	120VAC / 10A @ 120VAC
Outer Dimensions (Height x Width x Depth)	13.1 x 10.2 x 8.0 Inches (334 x 259 x 204 mm)
Inner Dimensions* (Height x Width x Depth)	8.5 x 7.5 x 5.8 Inches (216 x 190 x 147 mm)
Mounting Plate Material	0.06 in. (1.5 mm) Aluminum
Weight	4.0 lbs. (1.8 kg)
Power Cord Length	5 Feet (1.5m)
Ratings	Meets NEMA 3R, 3RX and IP24
Flame Rating	Meets UL94-V0

*Interior dimensions represent maximum space available for equipment.