## NP131004A1C

Altelix

13x10x4 NEMA 4X Polycarbonate + ABS Weatherproof Enclosure with Equipment Mounting Plate, 120VAC Outlet & Power Cord



## **Features**

- Features a 1.5mm Thick Finished Aluminum Equipment Mounting Plate with 120VAC
  Power Outlet
- Pre-wired 5 Foot Power Cord
- Meets NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66
- Weatherproof and UV Stable Durable Polycarbonate + ABS
- RF Transparent for Wireless Devices
- Gasketed Lid with Dual Latches
- Tamper-Proof Locking Screw with Key and Provision for Padlock
- Includes Wall Mounting Hardware, Cable Glands, Zip Ties, Cable Management Straps
- Optional Pole Mount Kit Available



## **Description**

The **Altelix NP131004A1C** Plastic Utility Enclosure is an industrial quality general purpose weatherproof utility box designed to offer extreme protection for wiring, electronics and wireless devices in harsh environments.

**Construction and Features -** This enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless steel security screw and provision for padlock. It meets or exceeds NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66.

**Power -** This configuration consists of the PC+ABS NEMA enclosure with hinged lid and a 1.5mm thick aluminum plate with a 120VAC power outlet. A 5 foot pre-wired power cord is included to power the enclosure, so no additional wiring is required. Cable glands on the enclosure allows cables to be connected to internal devices.

**Complete with Cable Glands and Wire Management Accessories -** This enclosure includes 3 weatherproof cable glands. Simply punch out the seal, run your cable, and hand tighten for a water-tight seal. For convenience, the included accessory kit contains wall anchors, zip ties, hook-and-loop wire management straps, door locking key and more.

## **Specifications**

Material	Polycarbonate + ABS
Color	Gray (Additional colors available – see Altelix.com)
Voltage / Max Load	120VAC / 10A @ 120VAC
Outer Dimensions (Height x Width x Depth)	13.7 x 10.8 x 4.1 Inches (348 x 274 x 104 mm)
Inner Dimensions* (Height x Width x Depth)	7.0 x 7.8 x 3.3 Inches (178 x 197 x 82 mm)
Mounting Plate Material	0.06 in. (1.5mm) Aluminum
Weight	3.2 lbs. (1.4 kg)
Power Cord Length	5 Feet (1.5m)
Ratings	Meets or Exceeds NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66
Flame Rating	Meets UL94-V0
Included Cable Glands	(3) M24 x 1.5

<sup>\*</sup>Interior dimensions represent maximum space available for equipment. See drawing for additional details.