

13x10x4 NEMA 4X Polycarbonate + ABS Weatherproof Enclosure with Non-Metallic Equipment Mounting Plate, 120VAC Outlet & Power Cord



Features

- No Electrical Wiring Required
- Pre-Wired 120VAC Power Outlet
- Pre-wired 5 Foot Power Cord
- PVC Non-Metallic Equipment Mounting Plate
- Meets NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66
- Weatherproof and UV Stable Durable Polycarbonate + ABS
- RF Transparent for Wireless Devices
- Gasketed Lid with Dual Latches
- Tamper-Proof Locking Screw with Key and Provision for Padlock
- Includes Wall Mounting Hardware, Cable Glands, Zip Ties, Cable Management Straps

Description

The **Altelix NP131004MA1C** NEMA 4X enclosure is simple to install because no wiring is required. Simply mount the enclosure and plug the pre-wired 5 foot power cord into a nearby outlet. The non-metallic equipment mounting plate features a pre-wired 120VAC power outlet for your equipment. Cable glands on the enclosure allows cables to be connected to internal devices.

Get your project up and running quickly and transition to hard-wired later if needed. The power cord can be removed and the power receptacle can be hard-wired by a qualified installer.

Construction and Features - This enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless steel security screw and provision for padlock. It meets or exceeds NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66.

RF Transparent Design - The NP131004MA1C is ideal for WiFi applications. The non-metallic design of both the enclosure and equipment mounting plate will not interfere the radio's operation. In addition, mounting radios to the PVC equipment mounting plate can be done simply by using self-tapping screws. The size of this enclosure will fit a wide range of popular wireless points on the market.

Complete with Cable Glands and Wire Management Accessories - This enclosure includes 3 weatherproof cable glands. Simply punch out the seal, run your cable, and hand tighten for a water-tight seal. For convenience, the included accessory kit contains wall anchors, zip ties, hook-and-loop wire management straps, door locking key and more.

Specifications

Material	Polycarbonate + ABS
Color	Gray
Voltage / Max Load	120VAC / 10A @ 120VAC
Outer Dimensions (Height x Width x Depth)	13.7 x 10.8 x 4.1 Inches (348 x 274 x 104 mm)
Inner Dimensions* (Height x Width x Depth)	7.0 x 7.8 x 3.1 Inches (178 x 197 x 79 mm)
Mounting Plate Material	0.25 in. (6.4mm) PVC Foam
Weight	3.2 lbs. (1.4 kg)
Power Cord Length	5 Feet (1.5m)
Ratings	Meets or Exceeds NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66
Flame Rating	Meets UL94-V0
Included Cable Glands	(3) M24 x 1.5

*Interior dimensions represent maximum space available for equipment. See drawing for additional details.