



## Features

- 1.5mm Thick Finished Aluminum Equipment Mounting Plate
- Meets NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66
- Weatherproof and UV Stable
- Durable Polycarbonate + ABS
- RF Transparent Enclosure for Wireless Devices
- Gasketed Lid with Dual Latches
- Tamper-Proof Locking Screw with Key and Provision for Padlock
- Includes Wall Mounting Hardware, Cable Glands, Zip Ties, Cable Management Straps

## Description

---

### Weatherproof Polycarbonate + ABS Construction for Extreme Durability

The **Altelix NP131004P** Plastic Utility Enclosure is an industrial quality general purpose weatherproof utility box designed to offer extreme protection for wiring, electronics and wireless devices in harsh environments.

### Construction and Features

This enclosure includes a 1.5mm thick finished aluminum equipment mounting plate. The enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless steel security screw and provision for padlock. It meets or exceeds NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66.

### Complete with Cable Glands and Wire Management Accessories

This enclosure includes 4 weatherproof cable glands. Simply punch out the seal, run your cable, and hand tighten for a water-tight seal. For convenience, the included accessory kit contains wall anchors, zip ties, hook-and-loop wire management straps, door locking key and more.

## Specifications

---

<b>Material</b>	Polycarbonate + ABS
<b>Color</b>	Gray (Additional colors available – see <a href="http://Altelix.com">Altelix.com</a> )
<b>Outer Dimensions</b> (Height x Width x Depth)	13.7 x 10.8 x 4.1 Inches (348 x 274 x 104 mm)
<b>Inner Dimensions*</b> (Height x Width x Depth)	10.5 x 7.8 x 3.1 Inches (267 x 197 x 80 mm)
<b>Mounting Plate Material</b>	0.06 in. (1.5mm) Aluminum
<b>Weight</b>	2.7 lbs. (1.2 kg)
<b>Ratings</b>	Meets or Exceeds NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66
<b>Flame Rating</b>	Meets UL94-V0
<b>Included Cable Glands</b>	(4) M24 x 1.5

\*Interior dimensions represent maximum space available for equipment.