## NP131004VA1C

Altelix

13x10x4 Vented Polycarbonate + ABS Weatherproof Enclosure with Equipment Mounting Plate, 120VAC Outlet & Power Cord



## **Features**

- (2) 3" Vents with Rain Shields
- Features a 1.5mm Thick Finished Aluminum Equipment Mounting Plate with 120VAC Power Outlet
- Pre-wired 5 Foot Power Cord
- Meets NEMA 3R, 3RX and IP24
- Weatherproof and UV Stable Durable Polycarbonate + ABS
- RF Transparent for Wireless Devices
- Gasketed Lid with Dual Latches
- Tamper-Proof Locking Screw with Key and Provision for Padlock
- Includes Wall Mounting Hardware, Cable Glands, Zip Ties, Cable Management Straps
- Optional Pole Mount Kit Available



## **Description**

The **Altelix NP131004VA1C** features two 3" inch air vents covered by rain shields, with cleanable screens. It is ideal for protecting small devices from harsh environments and tampering, while allowing ventilation for installed equipment or batteries.

**Construction and Features -** This enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless steel security screw and provision for padlock. It meets or exceeds NEMA 3R, 3RX IP24.

**Power -** This configuration consists of the PC+ABS NEMA enclosure with hinged lid and a 1.5mm thick aluminum plate with a 120VAC power outlet. A 5 foot pre-wired power cord is included to power the enclosure, so no additional wiring is required. Cable glands on the enclosure allows cables to be connected to internal devices.

**Complete with Cable Glands and Wire Management Accessories -** This enclosure includes 3 weatherproof cable glands. Simply punch out the seal, run your cable, and hand tighten for a water-tight seal. For convenience, the included accessory kit contains wall anchors, zip ties, hook-and-loop wire management straps, door locking key and more.

## **Specifications**

Material	Polycarbonate + ABS
Color	Gray (Additional colors available – see Altelix.com)
Voltage / Max Load	120VAC / 10A @ 120VAC
Outer Dimensions (Height x Width x Depth)	13.7 x 10.8 x 5.4 Inches (348 x 274 x 136 mm)
Inner Dimensions* (Height x Width x Depth)	7.0 x 7.8 x 3.3 Inches (178 x 197 x 82 mm)
Mounting Plate Material	0.06 in. (1.5mm) Aluminum
Weight	3.2 lbs. (1.4 kg)
Power Cord Length	5 Feet (1.5m)
Ratings	Meets or Exceeds NEMA 3R, 3RX and IP24
Flame Rating	Meets UL94-V0
Included Cable Glands	(3) M24 x 1.5

<sup>\*</sup>Interior dimensions represent maximum space available for equipment. See drawing for additional details.