



## Features

- (2) 3" Vents with Rain Shields and Screens
- 1.5mm Thick Finished Aluminum Equipment Mounting Plate
- Meets NEMA 3R, 3RX and IP24
- Weatherproof and UV Stable
- Durable Polycarbonate + ABS
- RF Transparent Enclosure for Wireless Devices
- Gasketed Lid with Dual Latches
- Tamper-Proof Locking Screw with Key and Provision for Padlock
- Includes Wall Mounting Hardware, Cable Glands, Zip Ties, Cable Management Straps

## Description

---

### Vented Weatherproof Polycarbonate + ABS Construction for Extreme Durability

The **Altelix NP131004VP** Plastic Utility Enclosure is an industrial quality general purpose weatherproof utility box designed to offer extreme protection for wiring, electronics and wireless devices in harsh environments. It features two 3" inch air vents covered by rain shields, with cleanable screens.

### Construction and Features

This enclosure includes a 1.5mm thick finished aluminum equipment mounting plate. The enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless steel security screw and provision for padlock. It meets or exceeds NEMA 3R, 3RX and IP24.

### Complete with Cable Glands and Wire Management Accessories

This enclosure includes 4 weatherproof cable glands. Simply punch out the seal, run your cable, and hand tighten for a water-tight seal. For convenience, the included accessory kit contains wall anchors, zip ties, hook-and-loop wire management straps, door locking key and more.

## Specifications

---

<b>Material</b>	Polycarbonate + ABS
<b>Color</b>	Gray (Additional colors available – see Altelix.com)
<b>Outer Dimensions</b> (Height x Width x Depth)	13.7 x 10.8 x 5.4 Inches (348 x 274 x 136 mm)
<b>Inner Dimensions*</b> (Height x Width x Depth)	10.5 x 7.8 x 3.3 Inches (267 x 197 x 83 mm)
<b>Mounting Plate Material</b>	0.06 in. (1.5mm) Aluminum
<b>Weight</b>	2.7 lbs. (1.2 kg)
<b>Ratings</b>	Meets or Exceeds NEMA 3R, 3RX and IP24
<b>Flame Rating</b>	Meets UL94-V0
<b>Included Cable Glands</b>	(4) M24 x 1.5

\*Interior dimensions represent maximum space available for equipment.