



Features

- (2) Pre-Wired Universal 100-240VAC Outlets
- Finished Aluminum Equipment Mounting Plate
- Weatherproof and UV Stable
- Durable Polycarbonate + ABS
- Gasketed Lid with Dual Latches
- Tamper-Proof Locking Screw with Key and Provision for Padlock
- Includes Wall Mounting Hardware, Cable Grommets and Cable Gland
- Knock-Out Holes on Top & Bottom
- Optional Pole Mounting Kits Available

Description

The **Altelix NP141105AU** NEMA enclosure features a 100-240VAC universal power outlet supporting multiple international power standards in addition to the USA:

- 110VAC 50/60Hz
- 115VAC 50/60Hz
- 220VAC 50/60Hz
- 230VAC 50/60Hz
- 240VAC 50/60Hz

Universal Power Outlet - The universal 100-240 VAC power outlet is compatible with the following plug types:

- UK/Ireland BS 1363
- Italy CEI 23-16/VII
- Denmark Afsnit 107-2-D1
- Euro plug (2-pin) CEE 7/16
- Australia Type I
- India BS 546
- *Swiss (2-pin) SEV 1011
- *Israel SI 32
- *North America (2-pin) NEMA 1-15 and (3-pin) NEMA 5-15
- *Continental Europe (Schuko) CEE 7
- *France/Belgium CEE 7

*Please refer to the safety notes in the Technical Specs

PC+ABS Polycarbonate / ABS Blend for Extreme Durability - These enclosures are molded out of UV resistant PC+ABS, a high-tech thermoplastic blend of polycarbonate and ABS which combines the best qualities of both into a single material. PC+ABS enclosures are superior to ABS enclosures because they maintain high toughness, durability, and dimensional stability even at extreme cold and hot temperatures.

Aluminum Equipment Mounting Plate - The enclosure includes an aluminum equipment mounting plate. The plate can be drilled by the installer to suit unique site requirements.

Mounting

The enclosure can be wall mounted using the included wall anchors. An optional pole mount kit is also available for installations on poles up to 8 inches in diameter.

Specifications

| | |
|---------------------------------------|---|
| Material | Fiberglass Reinforced Polyester |
| Color | Gray (See Altelix.com for full list of available colors) |
| Voltage | 110VAC 50/60Hz 115VAC 50/60Hz 220VAC 50/60Hz 230VAC 50/60Hz 240VAC 50/60Hz |
| Universal Outlet Compatibility | UK/Ireland BS 1363 Italy CEI 23-16/VII Denmark Afsnit 107-2-D1 Euro plug (2-pin) CEE 7/16 India BS 546 Australia Type I Swiss (2-pin) SEV 1011** Israel SI 32** North America (2-pin) NEMA 1-15** North America (3-pin) NEMA 5-15** Continental Europe (Schuko) CEE 7** France/Belgium CEE 7** |
| Outer Dimensions | 13.4 x 11.5 x 5.0 Inches (340 x 293 x 127 mm) |
| Inner Dimensions* | 9.5 x 8.0 x 4.0 Inches (241 x 203 x 101 mm) |
| Mounting Plate Material | 0.08 in (2.0 mm) Aluminum |
| Mounting Plate Dimensions | 11.7 x 9.0 in. (298 x 230 mm) |
| Weight | 4.1 lbs. (1.8 kg) |
| Ratings | NEMA Type 3, 3X / IP55 |
| Flame Rating | UL94-V0 |
| Knockout Sizes (Diameter) | (4) 0.62 in. (16 mm) (4) 1.02 in. (26 mm) (4) 1.30 in. (33 mm) |

*Interior dimensions represent maximum space available for equipment.

**Safety Notes:

1. In some countries (Swiss, Israel, and North America) there may be polarity differences. To avoid possible damage to a device, check the polarity of your power supply and that of your device before plugging it in to the Universal AC outlet and switching it on.
2. Some devices require they be grounded. Use caution with plugs from Continental Europe (Schuko) and France/Belgium for the Universal AC outlet does not allow for the grounding tabs or grounding pin.