



Features

- (2) 3" Vents with Rain Shields and Screens
- Includes (2) Galvanized Steel Pole Mount Brackets & (2) Stainless Steel Adjustable Bands
- Meets NEMA Type 3R, 3RX and IEC IP24
- Weatherproof and UV Stable
- Durable Polycarbonate + ABS
- RF Transparent for Wireless Devices
- Gasketed Lid with Dual Latches
- Tamper-Proof Locking Screw with Key and Provision for Padlock
- Includes Wall Mounting Hardware, Cable Grommets, Zip Ties, Cable Management Loops and, Ground Plate & Ground Wire
- Knock-Out Holes on Top & Bottom
- Optional Equipment Mounting Plates Available

Description

Weatherproof Polycarbonate + ABS Construction for Extreme Durability

The **Altelix NP141105V-PKIT** is an industrial quality general purpose vented weatherproof utility box designed for mounting to poles and posts. It features two 3 inch air vents covered by rain shields, with cleanable screens. It is ideal for protecting small devices from harsh environments and tampering, while allowing ventilation for installed equipment or batteries.

Construction and Features

This enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless-steel security screw and provision for a padlock. Knock-out holes are provided on the top and bottom. Meets or exceeds NEMA Type 3R, 3RX and IEC IP24.

Pole Mounting

The included Pole Mount Kit features (2) galvanized steel brackets and (2) stainless steel adjustable bands that accommodate poles up to 8 inches in diameter. For larger diameter poles, such as utility poles, longer bands can be used.

Complete with Cable Grommets and Wire Management Accessories

This enclosure includes an assortment of cable grommets that can be installed in the knock-out holes for a weather resistant seal. The included accessory kit contains wall anchors, zip ties, wire management loops, grounding plate and ground wire, door locking key and more.

Specifications

Material	Polycarbonate + ABS
Color	Gray (See Altelix.com for full list of available colors)
Outer Dimensions (Height x Width x Depth)	13.4 x 11.6 x 6.3 Inches (340 x 294 x 161 mm)
Inner Dimensions* (Height x Width x Depth)	12.0 x 8.0 x 4.0 Inches (305 x 203 x 102 mm)
Weight (Enclosure & Pole Mount)	4.2 lbs. (1.9 kg)
Ratings	NEMA Type 3R, 3RX / IP24
Flame Rating	Meets UL94-V0
Knockout Sizes (Diameter)	(4) 0.62 in. (16 mm) (4) 1.02 in. (26 mm) (4) 1.30 in. (33 mm)

*Interior dimensions represent maximum space available for equipment.