



Note: Cable grommets pre-installed in Gray enclosures only.

Features

- (2) 3" Vents with Rain Shields and Screens
- Meets NEMA Type 3R, 3RX and IEC IP24
- Weatherproof and UV Stable
- Durable Polycarbonate + ABS
- Includes (2) 35mm Top Hat DIN Rails and 2.0mm Thick Aluminum Equipment Mounting Plate
- Gasketed Lid with Dual Latches
- Tamper-Proof Locking Screw with Key and Provision for Padlock
- Includes Wall Mounting Hardware and Cable Grommets
- Knock-Out Holes on Top & Bottom
- Optional Pole Mount Kits Available

Description

The **Altelix NP141105VP-DIN** PC+ABS Vented Utility Enclosure is an industrial quality general purpose weatherproof utility box designed to offer extreme protection for DIN rail mounted devices in harsh environments.

The Altelix NP141105VP-DIN features two 3 inch air vents covered by rain shields with cleanable screens. It is ideal for protecting equipment while allowing ventilation for installed equipment or batteries.

Construction and Features - This enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless steel security screw and provision for a padlock. Knock-out holes are provided on the top and bottom. Meets or exceeds NEMA Type 3R, 3RX and IEC IP24.

Includes (2) 35mm DIN Rails and Aluminum Equipment Plate - Included with this enclosure are (2) 9" long 20-gauge steel 35mm top hat DIN rails. They easily attached to the 2.0mm thick aluminum equipment mounting plate included with the enclosure. Hardware for mounting the DIN rails and equipment mounting plate is included.

Complete with Cable Grommets and Wire Management Accessories - This enclosure includes an assortment of cable grommets that can be installed in the knock-out holes for a weather resistant seal. The included accessory kit contains wall anchors, zip ties, door locking key and more.

Specifications

Material	Polycarbonate + ABS
Color	Gray (See Altelix.com for full list of available colors)
Outer Dimensions (Height x Width x Depth)	13.4 x 11.6 x 6.3 Inches (340 x 294 x 161 mm)
Inner Dimensions* (Height x Width x Depth)	12.0 x 8.0 x 4.0 Inches (305 x 203 x 102 mm)
Mounting Plate Material	0.08 In. (2.0 mm) Aluminum
Mounting Plate Dimensions	9.0 x 11.7 In. (230 x 298 mm)
DIN Rail Length	9 In. (230 mm)
DIN Rail Material	20 Gauge (0.04 Inch) Steel
Weight	4.0 lbs. (1.7 kg)
Ratings	NEMA Type 3R, 3RX / IP24
Flame Rating	Meets UL94-V0
Knockout Sizes (Diameter)	(4) 0.62 in. (16 mm) (4) 1.02 in. (26 mm) (4) 1.30 in. (33 mm)

*Interior dimensions represent maximum space available for equipment.