



Note: Cable grommets pre-installed in Gray enclosures only.

Features

- (2) 3" Vents with Rain Shields and Screens
- Meets NEMA Type 3R, 3RX and IEC IP24
- Weatherproof and UV Stable
- Durable Polycarbonate + ABS
- Includes 2.0mm Thick Aluminum Equipment Mounting Plate
- Gasketed Lid with Dual Latches
- Tamper-Proof Locking Screw with Key and Provision for Padlock
- Includes Wall Mounting Hardware and Cable Grommets
- Knock-Out Holes on Top & Bottom
- Optional Pole Mount Kits Available

Description

The **Altelix NP141105VP** PC+ABS Plastic Vented Utility Enclosure is an industrial quality general purpose weatherproof utility box designed to offer extreme protection for wiring and small devices in harsh environments.

The Altelix NP141105VP features two 3 inch air vents covered by rain shields with cleanable screens. It is ideal for protecting equipment while allowing ventilation for installed equipment or batteries.

Construction and Features - This enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless steel security screw and provision for a padlock. Knock-out holes are provided on the top and bottom. Meets or exceeds NEMA Type 3R, 3RX and IEC IP24.

Aluminum Equipment Plate - This configuration consists of the PC+ABS enclosure with hinged lid and a 2.0mm thick aluminum plate for mounting and securing equipment. The enclosure and plate can be drilled and modified by the installer to suit unique site requirements.

Complete with Cable Grommets and Wire Management Accessories - This enclosure includes an assortment of cable grommets that can be installed in the knock-out holes for a weather resistant seal. The included accessory kit contains wall anchors, zip ties, door locking key and more.

Specifications

Material	Polycarbonate + ABS
Color	Gray (See Altelix.com for full list of available colors)
Outer Dimensions (Height x Width x Depth)	13.4 x 11.6 x 6.3 Inches (340 x 294 x 161 mm)
Inner Dimensions* (Height x Width x Depth)	12.0 x 8.0 x 4.0 Inches (305 x 203 x 102 mm)
Mounting Plate Material	0.08 In. (2.0 mm) Aluminum
Mounting Plate Dimensions	9.0 x 11.7 In. (230 x 298 mm)
Weight	4.0 lbs. (1.7 kg)
Ratings	NEMA Type 3R, 3RX / IP24
Flame Rating	Meets UL94-V0
Knockout Sizes (Diameter)	(4) 0.62 in. (16 mm) (4) 1.02 in. (26 mm) (4) 1.30 in. (33 mm)

*Interior dimensions represent maximum space available for equipment.