



## Features

- Features a 2.0mm Thick Finished Aluminum Equipment Mounting Plate with 120VAC Power Terminal Block
- Pre-wired 5 Foot Power Cord
- Meets NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66
- Weatherproof and UV Stable Durable Polycarbonate + ABS
- RF Transparent for Wireless Devices
- Gasketed Lid with Dual Latches
- Tamper-Proof Locking Screw with Key and Provision for Padlock
- Integral Mounting Feet
- Includes Wall Mounting Hardware, Cable Glands, Zip Ties, Cable Management Straps

## Description

---

The **Altelix NP151005A1C-0** Plastic Utility Enclosure is an industrial quality general purpose weatherproof utility box designed to offer extreme protection for wiring, electronics and wireless devices in harsh environments. It is designed for applications that do not require internal AC power outlets.

**Construction and Features** - This enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless steel security screw and provision for padlock. It meets or exceeds NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66.

**Power** - This configuration consists of the PC+ABS NEMA enclosure with hinged lid and a 2.0mm thick aluminum plate with a 120VAC power terminal block for hardwiring equipment power cords. A 5 foot pre-wired power cord is included to power the enclosure, so no additional wiring is required. A cable gland on the enclosure allows cables to be connected to internal devices. Additional cable glands are also provided on the enclosure for additional wiring.

**Complete with Cable Glands and Wire Management Accessories** - This enclosure includes 3 weatherproof cable glands. Simply punch out the seal, run your cable, and hand tighten for a water-tight seal. For convenience, the included accessory kit contains wall anchors, zip ties, hook-and-loop wire management straps, door locking key and more.

## Specifications

---

<b>Material</b>	Polycarbonate + ABS
<b>Color</b>	Gray
<b>Voltage / Max Load</b>	120VAC / 10A @ 120VAC
<b>Outer Dimensions</b> (Height x Width x Depth)	15.8 x 11.4 x 5.0 Inches (401 x 290 x 126 mm)
<b>Inner Dimensions*</b> (Height x Width x Depth)	9.8 x 8.0 x 4.0 Inches (248 x 203 x 101 mm)
<b>Mounting Plate Material</b>	0.08 in. (2.0mm) Aluminum
<b>Weight</b>	3.95 lbs. (1.8 kg)
<b>Power Cord Length</b>	5 Feet (1.5m)
<b>Ratings</b>	Meets or Exceeds NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66
<b>Flame Rating</b>	Meets UL94-V0

\*Interior dimensions represent maximum space available for equipment. See drawing for additional details.