



## Features

- (2) 3" Vents with a 120VAC Thermostat Controlled Cooling Fan
- Features a 2.0mm Thick Finished Aluminum Equipment Mounting Plate with Pre-wired 120VAC 3-Prong Power Plug
- Pre-wired 5 Foot Power Cord
- Meets NEMA 3R, 3RX and IP24
- Weatherproof and UV Stable Durable Polycarbonate + ABS
- RF Transparent for Wireless Devices
- Gasketed Lid with Dual Latches
- Tamper-Proof Locking Screw with Key and Provision for Padlock
- Integral Mounting Feet
- Includes Wall Mounting Hardware, Cable Glands, Zip Ties, Cable Management Straps

## Description

---

The **Altelix NP151005VFA1C-0C** features two 3" inch air vents and a 120VAC thermostat controlled cooling fan. It is ideal for protecting small devices from harsh environments and tampering, while allowing ventilation for installed equipment or batteries.

**Construction and Features** - This enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless steel security screw and provision for padlock. It meets or exceeds NEMA 3R, 3RX and IP24.

**Cooling Fan Ventilation** - The NP151005VFA1C-0C features two 3" inch air vents and a thermostat controlled cooling fan. The low noise, high airflow fan helps maintain lower internal temperatures. Rain shrouds on the front door keep rain water from entering the enclosure.

**120VAC Power** - This configuration consists of the PC+ABS NEMA enclosure with hinged lid and a 2.0mm thick aluminum plate with a pre-wired 120VAC 3-prong power plug. A 5 foot pre-wired power cord is included to power the enclosure, so no additional wiring is required. A cable gland on the enclosure allows cables to be connected to internal devices. Additional cable glands are also provided on the enclosure for additional wiring.

**Complete with Cable Glands and Wire Management Accessories** - This enclosure includes 3 weatherproof cable glands. Simply punch out the seal, run your cable, and hand tighten for a water-tight seal. For convenience, the included accessory kit contains wall anchors, zip ties, hook-and-loop wire management straps, door locking key and more.

## Specifications

---

<b>Material</b>	Polycarbonate + ABS
<b>Color</b>	Gray
<b>Voltage / Max Load</b>	120VAC / 10A @ 120VAC
<b>Cooling Fan Turn-On Temperature</b>	100°F (38°C)
<b>Cooling Fan Turn-Off Temperature</b>	79°F (26°C)
<b>Outer Dimensions</b> (Height x Width x Depth)	15.8 x 11.4 x 6.2 Inches (401 x 290 x 158 mm)
<b>Inner Dimensions*</b> (Height x Width x Depth)	9.8 x 8.0 x 2.8 Inches (248 x 203 x 71 mm)
<b>Mounting Plate Material</b>	0.08 in. (2.0mm) Aluminum
<b>Weight</b>	5.1 lbs. (2.3 kg)
<b>Power Cord Length</b>	5 Feet (1.5m)
<b>Ratings</b>	Meets or Exceeds NEMA 3R, 3RX and IP24
<b>Flame Rating</b>	Meets UL94-V0

\*Interior dimensions represent maximum space available for equipment. See drawing for additional details.