



Features

- (2) 3" Vents with Removable Filters
- 1.5mm Thick Finished Aluminum Equipment Mounting Plate
- Meets NEMA 3R, 3RX and IP24
- Weatherproof and UV Stable
- Durable Polycarbonate + ABS
- RF Transparent for Wireless Devices
- Gasketed Lid with Dual Latches
- Tamper-Proof Locking Screw with Key and Provision for Padlock
- Integral Mounting Feet
- Includes Wall Mounting Hardware, Cable Glands, Zip Ties, Cable Management Loops

Description

Vented Indoor Polycarbonate + ABS Construction for Extreme Durability

The **Altelix NP151005VP-IN** features two 3" inch air vents with removable filters. It is ideal for protecting small devices from theft and tampering, while allowing ventilation for installed equipment or batteries.

Construction and Features

This enclosure includes a 1.5mm thick finished aluminum equipment mounting plate. The enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless-steel security screw and provision for padlock. It meets or exceeds NEMA 3R, 3RX and IP24.

Complete with Cable Glands and Wire Management Accessories

This enclosure includes 4 weatherproof cable glands. Simply punch out the seal, run your cable, and hand tighten for a water-tight seal. For convenience, the included accessory kit contains wall anchors, zip ties, hook-and-loop wire management straps, door locking key and more.

Specifications

Material	Polycarbonate + ABS
Color	Gray
Outer Dimensions (Height x Width x Depth)	15.8 x 11.4 x 5.0 Inches (401 x 290 x 126 mm)
Inner Dimensions* (Height x Width x Depth)	11.8 x 8.0 x 3.8 Inches (298 x 203 x 97 mm)
Mounting Plate Material	0.06 in. (1.5mm) Aluminum
Weight	4.1 lbs. (1.8 kg)
Ratings	Meets or Exceeds NEMA 3R, 3RX and IP24
Flame Rating	Meets UL94-V0

*Interior dimensions represent maximum space available for equipment.