NP171403-DIN

Altelix 17x14x3 Polycarbonate Weatherproof DIN Rail Utility Enclosure



Features

- (2) 11" 35mm Top Hat DIN Rails
- Meets NEMA Type 3, 3X and IEC IP55
- Weatherproof and UV Stable
- Durable Polycarbonate + ABS Construction
- RF Transparent for Wireless Devices
- Raised Mounting Bosses for Equipment Mounting Plates and DIN Rails
- Gasket-Sealed Hinged Flat Lid with Dual Latches
- Tamper-Proof Locking Screw with Key and Provision for Padlock
- Includes Wall Mounting Hardware, Cable Grommets, Zip Ties, Cable Management Loops, Grounding Plate and Ground Wire
- Knockout Holes on Top and Bottom

Altelix LLC USA: 866-660-9434 +1 561-660-9434 sales@altelix.com www.altelix.com
Copyright (C) 2026 Altelix LLC. All rights reserved. Altelix and the Altelix logo are Trademarks and/or Registered Trademarks of Altelix LLC.
Specifications are subject to change without notice. See www.altelix.com for most current information.

NP171403-DIN

Description

Weatherproof Polycarbonate + ABS Construction For Extreme Durability
The Altelix 17x14x3 PC+ABS Utility Enclosure is an industrial-grade, general-purpose weatherproof enclosure designed to protect wiring, industrial controls and electronic devices in harsh environments. Includes (2) 11" 35mm Top Hat DIN rails. Available in Black or Gray with a choice of opaque or clear flat lid.

DIN Rail Equipment Mounting
This enclosure includes (2) 11" 35mm Top Hat DIN rails for mounting industrial controls, terminal blocks, relays and other DIN rail-mounted components. The rails allow equipment to be securely installed, positioned and replaced without drilling individual mounting holes.

Construction and Features
Molded from UV-resistant Polycarbonate + ABS for superior strength and durability, this enclosure features a gasket-sealed, hinged flat lid with dual latches, a stainless steel security screw and provision for a padlock. The clear lid option provides visibility of installed equipment without opening the enclosure. Knockout holes are provided on the top and bottom. Meets or exceeds NEMA Type 3, 3X and IEC IP55.

Complete with Cable Grommets and Wire Management Accessories
Includes an assortment of cable grommets for weather-resistant cable entry through the knockout holes. Supplied accessories include wall anchors, zip ties, wire management loops, grounding plate and ground wire, door locking key and more.

Optional Mounting Accessories
Pole mounting kits are available separately.

Copyright (C) 2026 Altelix LLC. All rights reserved. Altelix and the Altelix logo are Trademarks and/or Registered Trademarks of Altelix LLC.
Specifications are subject to change without notice. See www.altelix.com for most current information.

Product Photos



Altelix LLC USA: 866-660-9434 +1 561-660-9434 sales@altelix.com www.altelix.com
Copyright (C) 2026 Altelix LLC. All rights reserved. Altelix and the Altelix logo are Trademarks and/or Registered Trademarks of Altelix LLC.
Specifications are subject to change without notice. See www.altelix.com for most current information.

Specifications

Material	Polycarbonate + ABS
Available Colors	Black, Gray
Lid Options	Opaque, Clear
Outer Dimensions (Height x Width x Depth)	16.5 x 13.7 x 3.25 Inches (420 x 348 x 83 mm)
Inner Dimensions* (Height x Width x Depth)	14.0 x 9.0 x 2.75 Inches (356 x 229 x 70 mm)
DIN Rail Type	35mm Top Hat
DIN Rail Quantity	(2)
DIN Rail Length	11 in. (279 mm)
Weight	4.3 lbs. (2.0 kg)
Ratings	NEMA Type 3, 3X / IP55
Flame Rating	Meets UL94-V0
Knockout Sizes (Diameter)	(4) 0.62 in. (16 mm) (4) 1.02 in. (26 mm) (4) 1.30 in. (33 mm)

***Interior dimensions represent maximum space available for equipment.**

Altelix LLC USA: 866-660-9434 +1 561-660-9434 sales@altelix.com www.altelix.com
Copyright (C) 2026 Altelix LLC. All rights reserved. Altelix and the Altelix logo are Trademarks and/or Registered Trademarks of Altelix LLC.
Specifications are subject to change without notice. See www.altelix.com for most current information.