



Features

- (2) 3" Vents with Rain Shields and Screens
- Meets NEMA Type 3R, 3RX and IEC IP24
- Weatherproof and UV Stable
- Durable Polycarbonate + ABS
- RF Transparent for Wireless Devices
- Gasketed Lid with Dual Latches
- Tamper-Proof Locking Screw with Key and Provision for Padlock
- Includes Wall Mounting Hardware, Cable Grommets, Zip Ties, Cable Management Loops and, Ground Plate & Ground Wire
- Knock-Out Holes on Top & Bottom
- Optional Equipment Mounting Plates and Pole Mount Kits Available

Description

Polycarbonate + ABS Construction for Extreme Durability

The **Altelix NP171406V** PC+ABS Plastic Vented Utility Enclosure is an industrial quality general purpose weatherproof utility box designed to offer extreme protection for wiring and small devices in harsh environments.

The Altelix NP171406V features two 3 inch air vents covered by rain shields, with cleanable screens. It is ideal for protecting equipment while allowing ventilation for installed equipment or batteries.

Construction and Features

This enclosure is molded out of UV resistant Polycarbonate + ABS, an industrial grade plastic with greater strength and durability than standard ABS. It features a gasketed hinged door with dual latches, a stainless steel security screw and provision for a padlock. Knock-out holes are provided on the top and bottom. Meets or exceeds NEMA Type 3R, 3RX and IEC IP24.

Complete with Cable Grommets and Wire Management Accessories

This enclosure includes an assortment of cable grommets that can be installed in the knock-out holes for a weather resistant seal. The included accessory kit contains wall anchors, zip ties, wire management loops, grounding plate and ground wire, door locking key and more.

Specifications

Material	Polycarbonate + ABS
Available Colors	Gray, Black, Green, Red, Yellow
Outer Dimensions (Height x Width x Depth)	16.5 x 13.7 x 6.5 Inches (420 x 348 x 165 mm)
Inner Dimensions* (Height x Width x Depth)	14.0 x 9.0 x 4.3 Inches (356 x 229 x 108 mm)
Weight	4.4 lbs. (2.0 kg)
Ratings	NEMA Type 3R, 3RX / IP24
Flame Rating	Meets UL94-V0
Knockout Sizes (Diameter)	(4) 0.62 in. (16 mm) (4) 1.02 in. (26 mm) (4) 1.30 in. (33 mm)

*Interior dimensions represent maximum space available for equipment.