



Features

- Aluminum Mounting Plate with Wall Mount RJ11 Telephone Jack
- Available with either Service or Emergency Phone Labels
- For Telephones up to 4 Inches Depth
- Water Resistant Enclosure Design with Gasketed Lid
- NEMA Type 3, 3X / IP55 Rated
- UV and Corrosion Resistant
- Dust Proof and Vandal Resistant
- Durable PC+ABS Polycarbonate / ABS Blend Construction
- Includes Cable Grommets and Wall Mounting Hardware
- Optional Pole Mounting Kit Available

Description

The **Altelix TBP17** Weatherproof Phone Enclosure is ideal for deploying service and emergency telephones in outdoor locations and harsh environments such as in schools, on pool decks, golf courses, loading docks, public buildings and commercial properties.

This durable NEMA 3X enclosure is molded out of UV resistant PC+ABS, a high tech blend of polycarbonate and ABS which combines the best qualities of both into a single material. PC+ABS enclosures maintain high toughness, durability, and dimensional stability even at extreme cold and hot temperatures. The door is gasketed for use in dusty or wet areas.

Inside features an aluminum mounting plate with a standard RJ11 telephone wall mount jack. An aluminum wire cover and cable grommet are provided on the bottom of the enclosure for the telephone wire.

Mounting - The enclosure can be wall mounted using the included anchors. The mounting hardware is concealed within the enclosure for a finished appearance and enhanced security. An optional pole mount kit is also available.

Labels - The TBP17 is available with either a red and white Emergency Phone label or a green and white Service Phone label. Applied to the enclosure door, these labels are weatherproof and UV resistant.

Specifications

Models / Label	TBP17-1 / Emergency Phone Label TBP17-2 / Service Phone Label
Material	Polycarbonate + ABS
Available Colors	Gray, Light Ivory, OD Green
Outer Dimensions (Height x Width x Depth)	16.5 x 13.7 x 5.3 Inches (420 x 348 x 133 mm)
Inner Dimensions* (Height x Width x Depth)	14.0 x 9.0 x 4.0 Inches (356 x 229 x 101 mm)
Weight	5.1 lbs. (2.3 kg)
Ratings	NEMA Type 1, 2, 3, 3R, 3S, 3X / IP55
Flame Rating	Meets UL94-V0
Knockout Sizes (Diameter)	(4) 0.62 in. (16 mm) (4) 1.02 in. (26 mm) (4) 1.30 in. (33 mm)

*Interior dimensions represent maximum space available for equipment.