



Features

- Heavy Duty Continuous Seam Welded 18 Gauge Steel Construction
- Water Resistant Enclosure Design with Gasketed Lid
- Meets NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66
- Epoxy Polyester Textured Light Gray Powder Coat Finish
- Quarter-Turn Lockable Door Latch
- Standard Telephone Jack
- Service Phone Label Pre-Installed on Door
- Optional Pole Mounting Kit Available

Description

Construction and Features

This rugged IP66 rated enclosure features continuous seam welded 18 Gauge (1.2mm thick) steel construction. The enclosure door is fully gasketed making this enclosure suitable for use indoors or outdoors. The door features reinforced hinges and a quarter-turn latch to secure the enclosure. Internal grounding studs are provided on both the door enclosure. A removable access panel is provided and is fully gasketed to ensure proper seal.

Both the enclosure and door are finished in a rugged epoxy polyester textured light gray powder coat finish.

Telephone Jack

This model features a standard wall mount RJ11 jack. A cable gland is provided in the access panel on the bottom of the box for the telephone wire.

Lockable Latch

For additional protection, the box can be locked via use of a padlock (not included).

Service Phone Label

The TBS12-2 comes with an Service Phone label installed on the door of the box.

Mounting

This phone enclosure can be securely mounted to a wall or other structure. (4) mounting holes are provided inside the phone box. Optional flange and pole mounting kits are also available.

Specifications

Material	Continuous Seam Welded 18 Gauge (1.2 mm) Steel
Color	Light Gray (RAL 7035)
Outer Dimensions (Height x Width x Depth)	11.8 x 9.9 x 5.9 Inches (300 x 250 x 150 mm)
Inner Dimensions* (Height x Width x Depth)	8.3 x 6.3 x 4.8 Inches (210 x 159 x 121 mm)
Weight	9.3 lbs. (4.2 kg)
Ratings*	Meets or Exceeds NEMA 1, 2, 4, 4X, 12, 13 and IEC 529 IP65, IP66

*Notes:

- 1) Interior dimensions represent maximum space available for equipment.
- 2) Enclosure openings must be properly sealed with supplied plug to maintain NEMA Type 4, 4X / IP66 ratings.