



REV	DATE	DESCRIPTION
A	02/27/17	INITIAL RELEASE




THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ALTILIX LLC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF ALTILIX LLC IS PROHIBITED.



RG-8/X
RECOMMENDED CABLE
STRIPPING DIMENSIONS



LMR400
RECOMMENDED CABLE
STRIPPING DIMENSIONS



NO.	DESCRIPTION	MATERIAL	FINISH	QTY.
8	-	-	-	-
7	-	-	-	-
6	FERRULE	BRASS	NICKEL	1
5	SPACER	PTFE	-	1
4	CONTACT PIN	PHOSPHOR BRONZE	GOLD	1
3	BARREL	BRASS	NICKEL	1
2	DIELECTRIC	PTFE	-	1
1	SHELL/BODY	BRASS	NICKEL	1

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN MILLIMETERS.
DIMENSIONS IN [] ARE IN INCHES AND
ARE FOR CUSTOMER REFERENCE ONLY.

TOLERANCES FOR MILLIMETERS:
0.5-8mm 0.20mm
8-30mm 0.40mm
30-120mm 0.50mm

TASK	NAME	DATE
DRAWN BY	N.S.C.	02/09/17
CHECKED	-	-
APPROVED	-	-



1201 Clint Moore Road
Boca Raton, FL 33487
TEL: 561-660-WIFI

PART DESCRIPTION			N CRIMP JACK (240 SERIES, RG-8)		
PART NUMBER			CC240CNF		
DRAWING NUMBER			DRW-CC240CNF		
SCALE:	2:1	REV:	A	SHEET 1 OF 1	