	REV DATE		DESCRIPTION			THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ALTELIX LLC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF ALTELIX LLC IS PROHIBITED. ALL SPECIFICATION:
RECOMMENDED FERRULE CRIMP DIMENSIONS  RECOMMENDED CABLE STRIPPING DIMENSIONS  12,00,0,0)	A 05/15/17	INITIAL RELEASE	:			SUBJECT TO CHANGE WIHTOUT NOTICE. (C) 2017 ALTELIX LLC.
Altelix 1201 Clint Moore Roa Boca Raton, FL 33487 TEL: 561-660-WIFI	5/8-24UNEF-2A			16.03[0.63]	RECOMMENDED FERRULE CRIMP DIMENSIONS  SOLDER PIN	RECOMMENDED CABLE STRIPPING DIMENSIONS
L varay altaliy aan						Altelix 1201 Clint Moore Room Boca Raton, FL 33487 TEL: 561-660-WIFI

ı	NO.	DESCRIPTION	MATERIAL	FINISH	QTY.					PART DESCRIPTION	N		
t	8	-	-	-	-	UNLESS OTHERWISE SPECIFIED:	TASK NAME DATE			N-FEMALE CRIMP CONNECTOR 240 SERIES, RG-8			
Г	7	-	-	-	-	DIMENSIONS ARE IN MILLIMETERS.							
İ	6	-	-	-	-	DIMENSIONS IN [ ] ARE IN INCHES AND ARE FOR CUSTOMER REFERENCE ONLY.							
ı	5	-	-	-	-	ARE FOR COSTOMER REFERENCE ONET.	DRAWN BY	N COLUCCI	05/15/17	DADTAULADED			0.40015
Г	4	-	-	-	-	TOLERANCES FOR MILLIMETERS:	DRAWINDI	N. COLUCCI	05/15/17	PART NUMBER CC240CNF			
ľ	3	CONTACT PIN	BRASS	GOLD	1	0.5-8mm ± 0.20mm	CHECKED	-	-	DRAWING NUMBER DRW-CC24		CC240CNF	
L	2	FERRULE	BRASS	NICKEL	1	8-30mm ± 0.40mm				00.115	55) (		CLIEFT 1 OF 1
	1	BODY	BRASS	NICKEL	1	30-120mm ± 0.50mm	APPROVED	-	_	SCALE: 2:1	REV:	Α	SHEET 1 OF 1