



REV	DATE	DESCRIPTION
A	02/27/17	INITIAL RELEASE






THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ALTILIX LLC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF ALTILIX LLC IS PROHIBITED.



RG-8/X
RECOMMENDED CABLE
STRIPPING DIM'S



LMR400
RECOMMENDED CABLE
STRIPPING DIM'S



ITEM	DESCRIPTION	MATERIAL	FINISH	QTY.
9	SPACER	PTFE	-	1
8	FERRULE	BRASS	NICKEL	1
7	CONTACT PIN	BRASS	GOLD	1
6	RETAINER RING	STAINLESS STEEL	-	1
5	GASKET	SILICONE	-	1
4	DIELECTRIC	PTFE	-	1
3	BARREL	BRASS	NICKEL	1
2	BODY	BRASS	NICKEL	1
1	SHELL	BRASS	NICKEL	1

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN MILLIMETERS.
DIMENSIONS IN () ARE IN INCHES AND
ARE FOR CUSTOMER REFERENCE ONLY.

TOLERANCES FOR MILLIMETERS:
0.5-8mm 0.20mm
8-30mm 0.40mm
30-120mm 0.50mm

TASK	NAME	DATE
DRAWN BY	N.S.C.	02/10/17
CHECKED	-	-
APPROVED	-	-

Altelix
www.altelix.com

1201 Clint Moore Road
Boca Raton, FL 33487
TEL: 561-660-WIFI

PART DESCRIPTION

N CRIMP PLUG
(240 SERIES, RG-8/X)

PART NUMBER CC240CNM

DRAWING NUMBER DRW-CC240CNM

SCALE: 2:1 REV: A SHEET 1 OF 1