| REV | DATE | DESCRIPTION | | THE INFORMATION CONTAINED IN THIS DRAWING IS THE SO OF ALTELIX LLC. ANY REPRODUCTION IN PART OR WHOLE V WRITTEN PERMISSION OF ALTELIX LLC IS PROHIBITED. ALL SPE | WITHOUT THE |
|------|--------------|--------------------|--|---|-------------------------------|
| Α | 05/16/17 | INITIAL RELEASE | | SUBJECT TO CHANGE WIHTOUT NOTICE. (C) 2017 ALTE | ELIX LLC. |
| | | 3.500[0.138] | RECOMMENDED CABLE STRIPPING DIMENSIONS | RECOMMENDED FERRULE CRIMP SIZE | |
| | 1/4-36UNS-2B | 7,95[0.71] | SOLDERED CONTACT PIN 11.95 [0.47] | \$\tilde{\theta}_{0.09} \text{[0.07]} \\ \theta_{0.09} \text{[0.08]} \\ \theta_{0.09} \text{[0.09]} \\ \theta_{0.09} [0 | |
| ITEM | | SCRIPTION MATERIAL | FINISH QTY. | Atelix 1201 Clint Mo Boca Raton, I TEL: 561-660-V | oore Road FL 33487 WIFI |

| ITEM | DESCRIPTION | MATERIAL | FINISH | QTY. |
|------|-------------|----------|--------|------|
| 8 | - | - | - | - |
| 7 | i i | - | - | - |
| 6 | - | - | - | - |
| 5 | - | - | - | - |
| 4 | FERRULE | BRASS | NICKEL | 1 |
| 3 | CONTACT PIN | BRASS | GOLD | 1 |
| 2 | DIELECTRIC | PTFE | - | 1 |
| 1 | SHELL/BODY | BRASS | GOLD | 1 |

| UNLESS OTHERWISE SPECIFIED: | | | | |
|-------------------------------------|--|--|--|--|
| DIMENSIONS ARE IN MILLIMETERS. | | | | |
| DIMENSIONS IN [] ARE IN INCHES AND | | | | |
| ARE FOR CUSTOMER REFERENCE ONLY. | | | | |
| | | | | |
| TOLERANCES FOR MILLIMETERS: | | | | |
| $0.5-8$ mm ± 0.20 mm | | | | |
| 8-30mm ± 0.40mm | | | | |

30-120mm ± 0.50mm

| : | | | |
|---------|----------|------------|----------|
|) ′. | TASK | NAME | DATE |
| | DRAWN BY | N. COLUCCI | 05/16/17 |
| | CHECKED | - | - |

APPROVED

| | RPSMA-FEMALE CRIMP CONNECTOR | | | | | |
|----------|------------------------------|-----|------|---------------|--------------|--|
| DATE | 240 SERIES, RG-8 | | | | | |
| 05/16/17 | PART NUMBER | | | CC240CRSF | | |
| - | DRAWING NUMBER | | ER | DRW-CC240CRSF | | |
| - | SCALE: | 3:1 | REV: | Α | SHEET 1 OF 1 | |

PART DESCRIPTION