





REV	DATE	DESCRIPTION
A	02/27/17	INITIAL RELEASE

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ALTILIX LLC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF ALTILIX LLC IS PROHIBITED.



RECOMMENDED CABLE
STRIPPING DIMENSIONS



NO.	DESCRIPTION	MATERIAL	FINISH	QTY.
8	-	-	-	-
7	-	-	-	-
6	-	-	-	-
5	-	-	-	-
4	DIELECTRIC	PTFE	-	1
3	FERRULE	BRASS	NICKEL	1
2	CENTER PIN	BRASS	GOLD	1
1	BODY	BRASS	NICKEL	1

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN MILLIMETERS.
DIMENSIONS IN [] ARE IN INCHES AND
ARE FOR CUSTOMER REFERENCE ONLY.

TOLERANCES FOR MILLIMETERS:
0.5-8mm 0 0.20mm
8-30mm 0 0.40mm
30-120mm 0 0.50mm

TASK	NAME	DATE
DRAWN BY	N.S.C.	02/13/17
CHECKED	-	-
APPROVED	-	-

Altelix
www.altelix.com

1201 Clint Moore Road
Boca Raton, FL 33487
TEL: 561-660-WIFI

PART DESCRIPTION COAXIAL CRIMP CONNECTOR RPSMA-MALE (400 SERIES)		
PART NUMBER	CC400CRSM	
DRAWING NUMBER	DRW-CC400CRSM	
SCALE:	2:1	REV: A
SHEET 1 OF 1		