


A 07/17/17 INITIAL RELEASE	REV
A 0//1//1/ INITIAL RELEASE	A C


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ALTELIX LLC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF ALTELIX LLC IS PROHIBITED, ALL SPECIFICATIONS SUBJECT TO CHANGE WIHTOUT NOTICE. (C) 2017 ALTELIX LLC.






RECOMMENDED CABLE STRIPPING DIMENSIONS









PART DESCRIPTION

NO.	DESCRIPTION	MATERIAL	FINISH	QTY.
8	-	-	-	-
7	-	-	-	-
6	-	_	_	-
5	-	-	-	-
4	-	-	-	-
3	DIELECTRIC	PTFE	-	1
2	CENTER PIN	BRASS	SILVER	1
1	BODY	BRASS	TRI-METAL (CuSn7n3)	1

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND ARE FOR CUSTOMER REFERENCE ONLY. TOLERANCES FOR MILLIMETERS: 0.5-8mm ± 0.20mm 8-30mm ± 0.40mm

30-120mm ± 0.50mm

			LOVV	L 11/1/ 2	1017-10	1/AL
TASK	NAME	DATE			RC	34 0
DRAWN BY	N. COLUCCI	07/17/17	PART NU	MBER		
CHECKED	-	-	DRAWING	G NUMBI	ER	
APPROVED	-	-	SCALE:	3:1	REV:	Α

			LOW PIM SMA-MALE CONNECTO			ONNECTOR	
SK	NAME	DATE	RG402				
VN BY	N. COLUCCI	07/17/17	PART NU	MBER		CC	402XSM
CKED	-	-	DRAWING NUMBER		DRW-CC402XSM		
OVED	-	-	SCALE:	3:1	REV:	Α	SHEET 1 OF 1